

## Title (en)

METHOD FOR PREPARING A WOVEN, KNITTED OR NON WOVEN FIBROUS SUBSTRATE COATED ON ONE OR BOTH SIDES WITH AT LEAST ONE LAYER OF REINFORCED ELASTOMERIC SILICON

## Title (de)

VERFAHREN ZUR HERSTELLUNG EINES AUF EINER ODER BEIDEN SEITEN MIT MINDESTENS EINER SCHICHT AUS VERSTÄRKTEM ELASTOMERSILIKON BESCHICHTETEN WEB-, STRICK- ODER VLIESFASERSUBSTRATS

## Title (fr)

PROCÉDÉ POUR PRÉPARER UN SUPPORT FIBREUX TISSÉ, TRICOTÉ, OU NON TISSÉ ENDUIT SUR UNE OU DEUX FACES PAR AU MOINS UNE COUCHE SILICONE ÉLASTOMÉRIQUE RENFORCÉE

## Publication

**EP 2122046 A1 20091125 (FR)**

## Application

**EP 07857907 A 20071220**

## Priority

- EP 2007064286 W 20071220
- FR 0611272 A 20061222

## Abstract (en)

[origin: FR2910499A1] Preparing a woven, knitted or non-woven fibrous support coated on one or both sides by a reinforced elastomeric silicone layer comprises: preparing a silicone composition for crosslinkable coating (A) comprising organopolysiloxane for 100 parts by weight, a reinforcement constituted of polyamide microfibers; applying (A) on one or two sides of the woven, knitted or non-woven fibrous support; and crosslinking, preferably by heating or electromagnetic radiation of the deposit formed in applying step to form at least one reinforced elastomeric silicone layer. Preparing a woven, knitted or non-woven fibrous support coated on one or both sides by a reinforced elastomeric silicone layer comprises: preparing a silicone composition for crosslinkable coating (A) comprising organopolysiloxane of 0.5-15 parts by weight, preferably 2-6 parts by weight for 100 parts by weight, a reinforcement constituted of polyamide microfibers comprising a titre of 0.1-15 dtex, preferably 0.5-2.5 dtex, and length of 0.1-10 mm, preferably 0.2-5 mm; applying 20 g/m<sup>2</sup> of (A), preferably 100 g/m<sup>2</sup> on one or two sides of the woven, knitted or non-woven fibrous support; and crosslinking, preferably by heating or electromagnetic radiation of the deposit formed in applying step to form at least one reinforced elastomeric silicone layer, where the polyamide is nylon 6, polyamide 6.6, polyamide 4, polyamide 11, polyamide 12, polyamides 4-6, 6-10, 6-12, 6-36, 12-12 and their copolymers and mixtures. An independent claim is included for a woven, knitted or non-woven fibrous support coated on one or both sides, which is obtained by implementing the above process.

## IPC 8 full level

**D06N 3/12** (2006.01); **C08K 7/02** (2006.01); **C09D 183/04** (2006.01); **D06M 15/643** (2006.01)

## CPC (source: EP KR)

**C09D 183/04** (2013.01 - EP KR); **D06M 15/59** (2013.01 - EP KR); **D06M 15/643** (2013.01 - EP KR); **D06N 3/128** (2013.01 - EP KR); **D06M 2101/34** (2013.01 - KR); **D10B 2331/02** (2013.01 - KR)

## Citation (search report)

See references of WO 2008080867A1

## Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

## DOCDB simple family (publication)

**FR 2910499 A1 20080627**; EP 2122046 A1 20091125; KR 20090083938 A 20090804; WO 2008080867 A1 20080710

## DOCDB simple family (application)

**FR 0611272 A 20061222**; EP 07857907 A 20071220; EP 2007064286 W 20071220; KR 20097012885 A 20071220