

Title (en)

Method and base station for controlling beam forming in a mobile cellular network

Title (de)

Verfahren und Basisstation zur Steuerung einer Strahlbildung in einem mobilen zellularen Netzwerk

Title (fr)

Procédé et station de base pour contrôler la formation de faisceau dans un réseau cellulaire mobile

Publication

**EP 2129173 B1 20110720 (EN)**

Application

**EP 08290502 A 20080530**

Priority

EP 08290502 A 20080530

Abstract (en)

[origin: EP2129173A1] The invention concerns a method and a base station (21) for controlling beam forming in a mobile cellular network: Antenna units (212) of base stations (21) of a cluster of neighbored base stations (21) apply a respective beam pattern sequence on each sector of a cell served by the respective base station (21). The beam pattern sequence is selected from a respective predefined set of beam pattern sequences and each beam pattern sequence defines a sequence of beam subsets used for communication with mobile units (41, 42, 43, 44). One of the base stations (21) of the cluster which acts as trigger base station informs all neighbored base stations of the cluster of neighbored base stations (21, 22, 23, 24, 25, 26, 27) not to change their beam pattern sequences. The trigger base station (21) controls the antenna unit (212) of the trigger base station (21) to change the beam pattern sequence applied on the sectors of the cell and sequentially apply two or more different beam pattern sequences of the predefined set of beam pattern sequences on the respective sector. The trigger base station (21) triggers one or more mobile units (41, 42, 43, 44) located in the cluster of neighbored base stations to calculate one or more signal quality parameters for currently applied beam pattern sequences of the trigger base station (21). The trigger base station (21) selects an optimal beam pattern sequence from the set of the predefined beam pattern sequences based on the one or more calculated signal quality parameters and the antenna unit (212) of the trigger base station (21) applies the optimal beam pattern sequence as a new beam pattern sequence on the respective sector.

IPC 8 full level

**H04W 16/28** (2009.01); **H04B 7/04** (2006.01)

CPC (source: EP KR US)

**H01Q 1/246** (2013.01 - EP KR US); **H04B 7/0408** (2013.01 - KR); **H04B 7/0491** (2013.01 - KR); **H04B 7/0617** (2013.01 - EP KR US); **H04B 7/0695** (2013.01 - EP KR US); **H04L 25/0224** (2013.01 - KR); **H04W 16/28** (2013.01 - EP KR US); **H04W 84/042** (2013.01 - KR); **H04W 88/08** (2013.01 - KR); **H04B 7/0408** (2013.01 - EP US); **H04B 7/0491** (2013.01 - EP US); **H04W 84/042** (2013.01 - EP US); **H04W 88/08** (2013.01 - EP US)

Cited by

US2022191727A1; EP2979368A4; EP3082274A4; US11363470B1; GB2538772A; GB2538772B; EP2795808A4; WO2013094980A1; US9923682B2; US12119907B2; US9503913B2; US9210584B2; WO2012072101A1; WO2015119745A1; US9425929B2; EP3703271B1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 2129173 A1 20091202**; **EP 2129173 B1 20110720**; AT E517526 T1 20110815; CN 101594620 A 20091202; CN 101594620 B 20120704; JP 2011523818 A 20110818; JP 4975885 B2 20120711; KR 101136788 B1 20120419; KR 20100132071 A 20101216; US 2009296663 A1 20091203; US 8055303 B2 20111108; WO 2009144074 A1 20091203

DOCDB simple family (application)

**EP 08290502 A 20080530**; AT 08290502 T 20080530; CN 200910141649 A 20090525; EP 2009054241 W 20090408; JP 2011510917 A 20090408; KR 20107025136 A 20090408; US 47271209 A 20090527