

Title (en)
Oxygen administration apparatus

Title (de)
Sauerstoffverabreichungsvorrichtung

Title (fr)
Appareil d'administration d'oxygène

Publication
EP 2133113 B1 20120926 (EN)

Application
EP 09251355 A 20090520

Priority
• GB 0809392 A 20080523
• GB 0816626 A 20080911

Abstract (en)
[origin: EP2133113A1] An oxygen administration apparatus comprises a source of oxygen 2, an oxygen administration device 6, a flexible oxygen-conducting tubing 4 connectable at one end to the source of oxygen and an other end to the oxygen administration device 6. The connections are made through firebreaks 10 and 12. The firebreaks 10 and 12 are valves that both contain a fusible stop. In the event of a fire taking hold along the tubing 4, it travels back rapidly towards the source of oxygen 2. The resultant heat will cause the stop of the firebreak 12 to fuse, thereby closing off the supply of oxygen to the fire. If a fire takes hold downstream of the firebreak 10 then similarly the firebreak 10 closes off the supply of oxygen to the fire. The firebreaks 10 and 12 both have connecting ends of different configuration. The firebreak 10 is of different configuration from the firebreak 12.

IPC 8 full level
A61M 16/20 (2006.01); **A61M 16/10** (2006.01); **F16L 55/10** (2006.01)

CPC (source: EP US)
A61M 16/0672 (2014.02 - EP US); **A61M 16/0816** (2013.01 - EP US); **A61M 16/10** (2013.01 - EP US); **A61M 16/101** (2014.02 - EP US); **A61M 16/208** (2013.01 - EP US); **F16L 55/1022** (2013.01 - EP US); **F16L 55/1026** (2013.01 - EP US); **A61M 2202/0208** (2013.01 - EP US); **A61M 2205/3368** (2013.01 - EP US); **A62C 4/02** (2013.01 - EP US)

Cited by
US10406391B2; WO2014020334A1; WO2024002359A1; EP2520837A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 2133113 A1 20091216; EP 2133113 B1 20120926; DK 2133113 T3 20130114; US 2009288663 A1 20091126

DOCDB simple family (application)
EP 09251355 A 20090520; DK 09251355 T 20090520; US 46922709 A 20090520