

Title (en)

Method and device for cutting at least one side border of bound printed products

Title (de)

Verfahren und Vorrichtung für den Beschnitt wenigstens einer Seitenkante gebundener Druckerzeugnisse

Title (fr)

Procédé et dispositif pour la coupe d'au moins un bord latéral de produits d'impression reliés

Publication

**EP 2147759 B1 20131030 (DE)**

Application

**EP 08161112 A 20080724**

Priority

EP 08161112 A 20080724

Abstract (en)

[origin: EP2147759A1] The method involves feeding printed products in a cutting position on a cutting table. The side border is cut by a driven cutting blade retained by a pressure ram (5). The pressure ram exerts stretch force acting on an upper sheet of the printed product by impinging a surface area (9) on a printed product. An independent claim is included for a device for cutting a side border of bound printed products, and for use with a trimmer for printed products.

IPC 8 full level

**B26D 7/02** (2006.01); **B26D 1/09** (2006.01)

CPC (source: EP US)

**B26D 7/025** (2013.01 - EP US); **B26D 1/09** (2013.01 - EP US); **B26D 2007/0081** (2013.01 - EP US); **Y10T 83/04** (2015.04 - EP US); **Y10T 83/0448** (2015.04 - EP US); **Y10T 83/2066** (2015.04 - EP US); **Y10T 83/2068** (2015.04 - EP US); **Y10T 83/2183** (2015.04 - EP US); **Y10T 83/7573** (2015.04 - EP US); **Y10T 83/8723** (2015.04 - EP US)

Cited by

DE102010018879A1; EP2591896A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 2147759 A1 20100127**; **EP 2147759 B1 20131030**; JP 2010030037 A 20100212; JP 5506268 B2 20140528; US 2010018368 A1 20100128; US 8453547 B2 20130604

DOCDB simple family (application)

**EP 08161112 A 20080724**; JP 2009172586 A 20090723; US 50751109 A 20090722