

Title (en)

STRAIGHTENING MACHINE HAVING A STRAIGHTENING ROLLER RAPID-CHANGE SYSTEM, AND A METHOD FOR RAPIDLY CHANGING STRAIGHTENING ROLLERS OF A STRAIGHTENING MACHINE

Title (de)

RICHTMASCHINE MIT RICHTWALZEN-SCHNELLWECHSELSYSTEM SOWIE VERFAHREN ZUM SCHNELLEN WECHSELN VON RICHTWALZEN EINER RICHTMASCHINE

Title (fr)

MACHINE À DRESSER COMPRENANT UN SYSTÈME DE CHANGEMENT RAPIDE DE GALET DE DRESSAGE ET PROCÉDÉ DE CHANGEMENT RAPIDE DE GALETS DE DRESSAGE D'UNE MACHINE À DRESSER& xA;

Publication

EP 2162249 B1 20110921 (DE)

Application

EP 08758831 A 20080528

Priority

- EP 2008004248 W 20080528
- EP 07010704 A 20070530
- EP 08758831 A 20080528

Abstract (en)

[origin: WO2008145355A8] The present invention relates to a straightening machine (1) having a straightening roller rapid-change system, having an upper and a lower housing (7, 3) for receiving a plurality of upper and lower straightening rollers (9, 11), all or only some of which are driven and serve for straightening metallic material, wherein the upper and lower straightening rollers (9, 11) are mounted at each of their ends (56) and the driven straightening rollers are connected at one of their ends to a drive shaft (21, 23), and wherein the drive shafts (21, 23) can be driven via at least one distributor gearbox (19) by means of at least one motor (17), and the drive shafts (21, 23), the at least one distributor gearbox (19) and the at least one motor (17) are situated on one side of the straightening machine (1). The straightening machine according to the invention is distinguished in that the upper straightening rollers (9), at the side situated opposite the side of the drive shafts (21), are each rotatably mounted by means of at least one rolling bearing (39) in an upper, front bearing strip (25) which can be detachably connected to the upper housing (7), in that the lower straightening rollers (11), at the side situated opposite the side of the drive shafts (23), are each rotatably mounted by means of at least one rolling bearing (39) in a lower, front bearing strip (27) which can be detachably connected to the lower housing (3), in that, following removal of the upper/lower front bearing strip (25, 27), the upper/lower straightening rollers (9, 11) are accessible and can be moved individually out of the straightening machine by an axial movement, in that the straightening roller rapid-change system has a receiving device (59) for receiving the upper/lower straightening rollers (9, 11) that have been moved out, and in that the receiving device (59) has, for the purpose of mounting the straightening rollers (9, 11), a plurality of system strips (67, 68) which run transversely to the axial direction of the straightening rollers (9, 11) and have indentations (77) on their upper side for receiving the straightening rollers (9, 11). The present invention also relates to a method for rapidly changing straightening rollers of a straightening machine.

IPC 8 full level

B21D 1/02 (2006.01); **B21B 31/08** (2006.01); **B21B 31/10** (2006.01); **B21D 3/02** (2006.01); **B21D 3/05** (2006.01)

CPC (source: EP)

B21D 1/02 (2013.01); **B21D 37/14** (2013.01)

Cited by

CN109108108A; WO2014173756A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2008145355 A1 20081204; WO 2008145355 A8 20100304; AT E525146 T1 20111015; DK 2162249 T3 20120123; EP 2162249 A1 20100317; EP 2162249 B1 20110921; PL 2162249 T3 20120229

DOCDB simple family (application)

EP 2008004248 W 20080528; AT 08758831 T 20080528; DK 08758831 T 20080528; EP 08758831 A 20080528; PL 08758831 T 20080528