

Title (en)
Starting device

Title (de)
Startvorrichtung

Title (fr)
Dispositif de démarrage

Publication
EP 2172645 B1 20171025 (DE)

Application
EP 09167909 A 20090814

Priority
DE 102008042525 A 20081001

Abstract (en)
[origin: EP2172645A2] The device has a drive end bearing housing (19) in which a bearing (122) e.g. ball bearing, is fixed. The bearing indirectly supports a drive shaft (142). A starting pinion (22) is fastened to the drive shaft such that torque is transferable from the drive shaft to the starting pinion. The starting pinion has a front side (203), which is provided away from a drive of the device. A securing clip (209) i.e. snap ring, is stationary arranged on the drive shaft. A stopper ring (218) overlaps the securing clip by a single-piece formed collar (220) that is plastically deformed.

IPC 8 full level
F02N 11/00 (2006.01); **F02N 15/02** (2006.01); **F02N 15/06** (2006.01)

CPC (source: EP)
F02N 15/06 (2013.01); **F02N 11/00** (2013.01); **F02N 15/023** (2013.01)

Citation (examination)
DE 102006045753 A1 20070503 - DENSO CORP [JP]

Cited by
CN103154500A; EP2812563A4; EP2693043A4; US9617964B2; WO2012001023A3; WO2012146495A3; WO2012001025A3; US9518550B2; US10184443B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2172645 A2 20100407; **EP 2172645 A3 20150722**; **EP 2172645 B1 20171025**; DE 102008042525 A1 20100408; HU E038011 T2 20180928; JP 2010084769 A 20100415

DOCDB simple family (application)
EP 09167909 A 20090814; DE 102008042525 A 20081001; HU E09167909 A 20090814; JP 2009229368 A 20091001