

Title (en)

Machine tool and method for removing a workpiece part

Title (de)

Verfahren zum Entnehmen eines Werkstückteils und Werkzeugmaschine

Title (fr)

Procédé d'extraction d'une partie d'une pièce à usiner et machine-outil

Publication

EP 2177293 B1 20130102 (DE)

Application

EP 08018193 A 20081017

Priority

EP 08018193 A 20081017

Abstract (en)

[origin: EP2177293A1] The method for removing a workpiece part (15), which is formed by separately processing a plate-like workpiece lying on a workpiece support (5) of a tool machine, from a remaining workpiece (14), comprises lifting the workpiece part on its lower side by a height-adjustable support element (13) for moving an edge region (19) of the workpiece part into a removal position above the remaining workpiece, and positioning the workpiece part on the support element in a preceding step by displacing the workpiece support and/or workpiece part jointly with the remaining workpiece on the support. The method for removing a workpiece part (15), which is formed by separately processing a plate-like workpiece lying on a workpiece support (5) of a tool machine, from a remaining workpiece (14), comprises lifting the workpiece part on its lower side by a height-adjustable support element (13) for moving an edge region (19) of the workpiece part into a removal position above the remaining workpiece, and positioning the workpiece part on the support element in a preceding step by displacing the workpiece support and/or the workpiece part jointly with the remaining workpiece on the workpiece support. The support element is formed in an operating position of the workpiece support, and is formed by a punch matrix or a laser matrix of the tool machine. The lifting of the workpiece part takes place in the removal position selectively with a linear movement or a tilting movement. Connection paths, one of which is broken during lifting the workpiece part, remain between the workpiece part and the remaining workpiece during the separate processing. The workpiece part is tilted around a tilting axis during lifting. The tilting axis passes along the connection paths remaining between the workpiece part and the remaining workpiece during the separate processing. During lifting, the workpiece part is held on the support element by a suction device or a punching head provided at the operating position. The workpiece part is removed at the removal position using the suction device or a gripper. An independent claim is included for a tool machine.

IPC 8 full level

B21D 45/02 (2006.01); **B21D 24/02** (2006.01); **B21D 28/00** (2006.01); **B23K 26/08** (2006.01); **B23Q 1/68** (2006.01); **B23Q 7/00** (2006.01); **B26D 7/18** (2006.01)

CPC (source: EP)

B21D 45/02 (2013.01); **B23D 31/002** (2013.01); **B23K 26/083** (2013.01); **B23K 26/16** (2013.01); **B23K 26/702** (2015.10); **B23K 37/0408** (2013.01)

Cited by

DE102017216828A1; DE102017216828B4; DE102014209811A1; WO2014023323A1; US2015306653A1; DE102017114728B3; DE102018121968A1; EP2638986A1; US10449592B2; CN109789475A; JP2019529124A; EP3546111A1; EP4219066A3; DE102014209811B4; CN106794509A; JP2017516665A; DE102015207124B3; EP3546114A1; US9656315B2; DE112016000082B4; WO2020052848A1; US10207308B2; WO2013135572A1; WO2018055178A1; WO2015176931A1; WO2019057432A1; DE202014010730U1; US10512965B2; WO2019185617A1; WO2019185619A1; EP3723936B1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 2177293 A1 20100421; EP 2177293 B1 20130102

DOCDB simple family (application)

EP 08018193 A 20081017