

Title (en)
Clamping device for a covering element

Title (de)
Festhalteeinrichtung für eine Jalousie

Title (fr)
Dispositif d'arrêt pour volet roulant

Publication
EP 2177707 B1 20120808 (EN)

Application
EP 09173167 A 20091015

Priority
IT UD20080219 A 20081016

Abstract (en)
[origin: EP2177707A1] Clamping device for a covering element (12), selectively movable between at least a closed position in which it is disposed folded back, and an open position in which it is disposed extended in order to protect a predetermined surface from exposure to the sun or bad weather conditions, comprising first attachment means (13), associated with a lower terminal portion (17) of the covering element (12). The clamping device also comprises second attachment means (19), disposed on the ground or on a reference plane (P) associated with the surface, able to cooperate with the first attachment means (13) in order to keep the covering element (12) in the open position, The first and second attachment means (13, 19) comprise respective and mating magnetic attraction means able to achieve a mechanical coupling so as to keep the covering element (12) in its open position at a predetermined tension. The second attachment means (19) are provided with elastic means (29), able to allow a certain travel with respect to the ground or to said reference plane (P) on which they are mounted so as to compensate uncontrolled movements of the covering element (12).

IPC 8 full level
E06B 9/42 (2006.01); **E05C 19/16** (2006.01)

CPC (source: EP)
E06B 9/42 (2013.01); **E06B 2009/583** (2013.01)

Cited by
US2015275571A1; US9670721B2; JP2015229871A

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2177707 A1 20100421; EP 2177707 B1 20120808; ES 2392745 T3 20121213; IT 1391305 B1 20111201; IT UD20080219 A1 20100417

DOCDB simple family (application)
EP 09173167 A 20091015; ES 09173167 T 20091015; IT UD20080219 A 20081016