

Title (en)  
Cylinder for a large diesel motor

Title (de)  
Zylinder für einen Grossdieselmotor

Title (fr)  
Cylindre pour un grand moteur diesel

Publication  
**EP 2182094 A1 20100505 (DE)**

Application  
**EP 08168067 A 20081031**

Priority  
EP 08168067 A 20081031

Abstract (en)  
The cylinder (1) comprises a wall (2), whose surface forms a guide area, a piston (3) that is movably arranged along the guide area in back and forth manner and limits a combustion chamber (4), and a sacrificial anode, which is arranged such that it protects the guide area from corrosion. The sacrificial anode is equipped on the piston and is arranged as circular band, which encloses the piston in circumference direction. A circumferential groove is equipped as dovetail grooves to the piston, in which the sacrificial anode is arranged. The cylinder (1) comprises a wall (2), whose surface forms a guide area, a piston (3) that is movably arranged along the guide area in back and forth manner and limits a combustion chamber (4), and a sacrificial anode, which is arranged such that it protects the guide area from corrosion. The sacrificial anode is equipped on the piston and is arranged as circular band, which encloses the piston in circumference direction. A circumferential groove is equipped as dovetail grooves to the piston, in which the sacrificial anode is arranged. The piston has piston rings (31) over an electrically conductive element such as spring element connected with the piston, which biases the sacrificial anode in the direction of the guide area. The sacrificial anode is equipped at the side of the piston rings removable from the combustion chamber. The sacrificial anodes are provided in the wall of the cylinder, extend up to the guide area and are distributed over the circumference of the wall of the cylinder.

Abstract (de)  
Es wird ein Zylinder für einen Grossdieselmotor vorgeschlagen mit einer Wandung (2), deren Oberfläche eine Lauffläche (21) bildet und mit einem Kolben (3), der entlang der Lauffläche (21) hin und her bewegbar angeordnet ist und einen Brennraum (4) begrenzt. Es ist mindestens eine Opferanode (32) vorgesehen, welche so angeordnet ist, dass sie die Lauffläche (21) vor Korrosion schützt.

IPC 8 full level  
**C23F 13/02** (2006.01); **F02B 77/02** (2006.01); **F02F 1/00** (2006.01); **F02F 3/00** (2006.01); **F16J 9/20** (2006.01)

CPC (source: EP)  
**C23F 13/10** (2013.01); **C23F 13/18** (2013.01); **F02B 77/04** (2013.01); **F02F 1/18** (2013.01)

Citation (search report)  
• [X] JP H0526112 A 19930202 - TOYOTA MOTOR CORP, et al  
• [X] WO 0040850 A1 20000713 - MAN B & W DIESEL GMBH [DK], et al  
• [X] RU 2302480 C2 20070710 - SHARIFULLIN AGZAMNUR MUKHAMATG [RU]  
• [A] EP 1936245 A1 20080625 - WAERTSILAE NSD SCHWEIZ AG [CH]  
• [A] DE 6943852 U 19700312 - RUHRGAS AG [DE]  
• [A] WO 03067052 A1 20030814 - MAN B & W DIESEL AS [DK], et al  
• [A] EP 1898065 A1 20080312 - WAERTSILAE NSD SCHWEIZ AG [CH]  
• [A] EP 1762756 A2 20070314 - WAERTSILAE NSD SCHWEIZ AG [CH]  
• [A] EP 1752560 A1 20070214 - WAERTSILAE NSD SCHWEIZ AG [CH]

Cited by  
CN108823575A; FR3034827A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)  
AL BA MK RS

DOCDB simple family (publication)  
**EP 2182094 A1 20100505**

DOCDB simple family (application)  
**EP 08168067 A 20081031**