

Title (en)
Lock casing

Title (de)
Schließkasten

Title (fr)
Boîtier de verrou

Publication
EP 2184425 B1 20110928 (EN)

Application
EP 09175078 A 20091105

Priority
FI 20086065 A 20081111

Abstract (en)
[origin: EP2184425A1] A lock casing (1) having a bolt (8) that comprises a bolt body (8b) inside the lock casing and a bolt end (8a) that in its locking position protrudes out of a bolt opening (2a) in the lock casing's front plate (2), at least one operating axis (3), transmission means (4, 5, 7, 9) for moving the bolt and means (6, 7, 7b, 9) for deadlocking the bolt. There is a preferably plate-like protective piece between the lock casing (1) and the bolt body (8b), and it is arranged to prevent a tool or similar item to be inserted through the bolt opening (2a) into the lock casing (1) in a position that affects the deadlocking means (6, 7, 7b, 9). The protective piece (10) is supported on the bolt (8) so that it moves together with the bolt (8).

IPC 8 full level
E05B 17/20 (2006.01); **E05B 63/00** (2006.01)

CPC (source: EP FI)
E05B 15/10 (2013.01 - EP); **E05B 17/2003** (2013.01 - EP FI); **E05B 17/2034** (2013.01 - EP); **E05B 17/2057** (2013.01 - FI);
E05B 63/0017 (2013.01 - EP); **E05B 17/2084** (2013.01 - EP)

Cited by
CN105545183A; EP2907944A1; WO2011120845A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)
EP 2184425 A1 20100512; **EP 2184425 B1 20110928**; AT E526475 T1 20111015; DK 2184425 T3 20111121; FI 121577 B 20110114;
FI 20086065 A0 20081111; FI 20086065 A 20100512; RU 2009141637 A 20110520; RU 2508435 C2 20140227

DOCDB simple family (application)
EP 09175078 A 20091105; AT 09175078 T 20091105; DK 09175078 T 20091105; FI 20086065 A 20081111; RU 2009141637 A 20091110