

Title (en)

TAMPER-RESISTANT ARTICLE SECURITY DEVICE AND METHOD

Title (de)

VORRICHTUNG UND VERFAHREN ZUR MANIPULATIONSSICHEREN ARTIKELSICHERUNGSVORRICHTUNG

Title (fr)

DISPOSITIF ET PROCÉDÉ DE SÉCURITÉ D'ARTICLE INVOLABLE

Publication

EP 2185780 A1 20100519 (EN)

Application

EP 08794886 A 20080730

Priority

- US 2008009217 W 20080730
- US 96741607 P 20070904
- US 2836708 P 20080213

Abstract (en)

[origin: WO2009032038A1] A method and device for protecting an article, wherein the security device has belt having a latch mating element. A magnetically actuatable locking mechanism has a magnetically actuatable latch and a flexible element. The magnetically actuatable latch includes a lower surface having at least one protrusion extending there from and adapted to engage with the latch mating element of the belt, and a front surface adjacent the lower surface. The front surface has a lateral notch formed therein. The flexible element biases the magnetically actuatable latch and the belt into a locked position. A housing has the magnetically actuatable latch disposed therein and housing includes a passageway therein defining a belt pathway configured to slidably receive the belt therein.

IPC 8 full level

E05B 73/00 (2006.01)

CPC (source: EP)

E05B 73/00 (2013.01); **E05B 73/0041** (2013.01); **E05B 15/0046** (2013.01)

Citation (search report)

See references of WO 2009032038A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

WO 2009032038 A1 20090312; CA 2698394 A1 20090312; CA 2698394 C 20150519; CN 101809244 A 20100818; CN 101809244 B 20130918; EP 2185780 A1 20100519; EP 2185780 B1 20121205; ES 2399772 T3 20130403; HK 1144455 A1 20110218

DOCDB simple family (application)

US 2008009217 W 20080730; CA 2698394 A 20080730; CN 200880105566 A 20080730; EP 08794886 A 20080730; ES 08794886 T 20080730; HK 10110940 A 20101125