

Title (en)

FLEXURE SEAL FOR FUEL INJECTION NOZZLE

Title (de)

FLEXURDICHTUNG FÜR KRAFTSTOFFEINSPRITZDÜSE

Title (fr)

JOINT DE FLEXURE POUR LA BUSE D'INJECTION DE CARBURANT

Publication

**EP 2188569 A2 20100526 (EN)**

Application

**EP 08832161 A 20080917**

Priority

- US 2008076610 W 20080917
- US 99405307 P 20070917

Abstract (en)

[origin: WO2009039142A2] A nozzle includes an inlet at an upstream end of the nozzle, a discharge outlet at a downstream end of the nozzle, and a fluid delivery passage extending between the inlet and the discharge outlet. Exterior and interior walls of the nozzle have downstream tip ends that are relatively longitudinally movable at one or more interfaces. An internal insulating gap is interposed between the interior and exterior walls to insulate fuel from ambient temperature conditions exterior to the nozzle. One or more flexible seal structures internal to the nozzle isolate a portion of the insulating gap from any ambient fluid entering into the gap through the one or more interfaces while providing relative movement between interior and exterior walls of the nozzle.

IPC 8 full level

**F23D 11/38** (2006.01); **F23R 3/28** (2006.01)

CPC (source: EP)

**F23D 11/38** (2013.01); **F23R 3/283** (2013.01); **F23R 3/286** (2013.01); **F23D 2211/00** (2013.01); **F23D 2900/00016** (2013.01); **F23D 2900/11101** (2013.01)

Citation (search report)

See references of WO 2009039142A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

**WO 2009039142 A2 20090326**; **WO 2009039142 A3 20100415**; EP 2188569 A2 20100526; EP 2188569 B1 20180425; EP 3425275 A1 20190109; EP 3425275 B1 20201118

DOCDB simple family (application)

**US 2008076610 W 20080917**; EP 08832161 A 20080917; EP 18169078 A 20080917