

Title (en)

METHOD AND DEVICE FOR THE ELECTROMAGNETIC STIRRING OF ELECTRICALLY CONDUCTIVE FLUIDS

Title (de)

VERFAHREN UND EINRICHTUNG ZUM ELEKTROMAGNETISCHEN RÜHREN VON ELEKTRISCH LEITENDEN FLÜSSIGKEITEN

Title (fr)

PROCÉDÉ ET MODULE D'AGITATION ÉLECTROMAGNÉTIQUE DE LIQUIDES ÉLECTRIQUEMENT CONDUCTEURS

Publication

EP 2190612 A1 20100602 (DE)

Application

EP 08801098 A 20080801

Priority

- DE 2008001260 W 20080801
- DE 102007037340 A 20070803

Abstract (en)

[origin: WO2009018809A1] The invention relates to a method and to a device for the electromagnetic stirring of electrically conductive fluids (2, 21, 22) in the liquid state and/or in the state of onsetting solidification of the fluid (2, 21, 22), using a rotating magnetic field that is produced in the horizontal plane of a Lorentz force (FL). The aim is to achieve an intensive three-dimensional flow on the inside of the fluid for mixing in the liquid state up to the direct vicinity of solidifying fronts, and to simultaneously ensure an undisturbed, free surface of the fluid. The solution is to change the direction of rotation (15, 16) of the magnetic field rotating in the horizontal plane at regular time intervals in the form of a period duration (TP), wherein the frequency of the directional change of movement of the magnetic field vector is adjusted such that in the state of mixing the liquid fluid (2, 21, 22) a period duration (TP) is adjusted between two directional changes of the magnetic field during a time interval (?TPM) as a function of the adjustment time (ti.a.) with the condition (I) $0.5 \cdot ti.a \leq PM \leq i.a$ and such that, at the beginning of the state of onsetting solidification of the fluid (2,21,22), a period duration (Tp) is set between two directional changes of the magnetic field in a time interval (?TPE) as a function of the adjustment time (ti.a.) with the condition (II) $0.8 \cdot ti.a \leq PE \leq i.a$, wherein the adjustment time (ti.a) is specified by the equation (III) in which after an activation of the rotating magnetic field in a fluid (2; 21, 22) in the resting state the double vortex of the meridional secondary flow (18) forms, and in which s is defined as the electric conductivity, ρ as the density of the fluid (2, 21, 22), ω as the frequency, Bo as the amplitude of the magnetic field, and C9 as the constant for the influence of the size and shape of the volume of the fluid (2, 21, 22).

IPC 8 full level

B22D 27/02 (2006.01); **B22D 27/04** (2006.01)

CPC (source: EP US)

B01F 33/451 (2022.01 - US); **B22D 27/02** (2013.01 - EP US); **B22D 27/045** (2013.01 - EP US); **C21C 1/06** (2013.01 - EP US); **F27D 27/00** (2013.01 - EP US); **Y10T 137/0391** (2015.04 - EP US); **Y10T 137/206** (2015.04 - EP US)

Citation (search report)

See references of WO 2009018809A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

WO 2009018809 A1 20090212; DE 102007037340 A1 20090219; DE 102007037340 B4 20100225; EP 2190612 A1 20100602; EP 2190612 B1 20171220; JP 2010535105 A 20101118; JP 5124863 B2 20130123; US 2011297239 A1 20111208; US 2014290433 A1 20141002; US 8944142 B2 20150203

DOCDB simple family (application)

DE 2008001260 W 20080801; DE 102007037340 A 20070803; EP 08801098 A 20080801; JP 2010518494 A 20080801; US 201314094350 A 20131202; US 67203608 A 20080801