

Title (en)
Steel alloy for machine components

Title (de)
Stahllegierung für Maschinenkomponenten

Title (fr)
Alliage d'acier pour composants de machines

Publication
EP 2196553 A1 20100616 (DE)

Application
EP 09450220 A 20091123

Priority
AT 19042008 A 20081205

Abstract (en)
The machine component or component consists of thermally hardened steel alloy having carbon (0.48-0.55 wt.%), silicon (0.18-0.25 wt.%), manganese (0.35-0.45 wt.%), chromium (4.40-4.70 wt.%), molybdenum (2.90-3.10 wt.%), vanadium (0.72-0.77 wt.%), iron and accompanying elements necessitated by steel production and impurities as remainder. The accompanying elements or impurity elements consist of phosphorus (0.005 wt.%), sulfur (0.001 wt.%), nickel (0.1 wt.%), copper (0.1 wt.%), cobalt (0.1 wt.%), titanium (0.005 wt.%), aluminum (0.01 wt.%), nitrogen (0.003 wt.%) and oxygen (0.002 wt.%). The machine component or component consists of thermally hardened steel alloy having carbon (0.48-0.55 wt.%), silicon (0.18-0.25 wt.%), manganese (0.35-0.45 wt.%), chromium (4.40-4.70 wt.%), molybdenum (2.90-3.10 wt.%), vanadium (0.72-0.77 wt.%), iron and accompanying elements necessitated by steel production and impurities as remainder. The accompanying elements or impurity elements consist of phosphorus (0.005 wt.%), sulfur (0.001 wt.%), nickel (0.1 wt.%), copper (0.1 wt.%), cobalt (0.1 wt.%), titanium (0.005 wt.%), aluminum (0.01 wt.%), nitrogen (0.003 wt.%), oxygen (0.002 wt.%), calcium (0.001 wt.%), magnesium (0.001 wt.%) and tin (0.005 wt.%). The component has a purity degree of steel alloy. The elasticity module of the material is 205000 MPa. The machine component has a tensile strength of greater than 2000 MPa for changing mechanical loads to a temperature of greater than 160[deg] C, and a hardness of greater than 55 [HRC] produced by thermal tempering.

Abstract (de)
Die Erfindung bezieht sich auf Maschinenkomponenten oder Bauteile mit einer Festigkeit von größer 2000 [MPa] für wechselnde, mechanische Belastungen bis zu einer Temperatur von 160 °C, gebildet aus einer thermisch vergüteten Stahllegierung. Um verbesserte Langzeiteigenschaften, insbesondere Ermüdungssicherheit bei hohen Beanspruchungen auf einen höheren E-Modul des Werkstoffes zu erreichen, ist gemäß der Erfindung vorgesehen, dass die Stahllegierung eine chemische Zusammensetzung in Gew.-% von Kohlenstoff (C) 0.48 bis 0.55 Silicium (Si) 0.18 bis 0.25 Mangan (Ma) 0.35 bis 0.45 Chrom (Cr) 4.40 bis 4.70 Molybdän (Mo) 2.90 bis 3.10 Vanadin (V) 0.72 bis 0.77 Eisen (Fe) und erschmelzungsbedingte Begleitelemente und Verunreinigungen als Rest besitzt.

IPC 8 full level
C22C 38/00 (2006.01); **C22C 38/22** (2006.01); **C22C 38/24** (2006.01)

CPC (source: EP US)
C22C 38/22 (2013.01 - EP US); **C22C 38/24** (2013.01 - EP US)

Citation (applicant)
• EP 1300482 A1 20030409 - BOEHLER EDELSTAHL [AT]
• JP 2004169177 A 20040617 - DAIDO STEEL CO LTD
• JP H10121201 A 19980512 - KOBE STEEL LTD
• JP 2002121648 A 20020426 - SANYO SPECIAL STEEL CO LTD

Citation (search report)
• [A] EP 1300482 A1 20030409 - BOEHLER EDELSTAHL [AT]
• [A] JP H10121201 A 19980512 - KOBE STEEL LTD
• [A] JP 2004169177 A 20040617 - DAIDO STEEL CO LTD
• [A] JP 2002121648 A 20020426 - SANYO SPECIAL STEEL CO LTD

Cited by
CN102445486A; WO2017116367A1; EP3050986B1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
EP 2196553 A1 20100616; **EP 2196553 B1 20141008**; AT 507597 A1 20100615; AT 507597 B1 20100915; AU 2009240807 A1 20100624; AU 2009240807 B2 20110519; BR PI0905064 A2 20110208; CA 2686594 A1 20100605; CA 2686594 C 20160920; ES 2526865 T3 20150116; PL 2196553 T3 20150331; SI 2196553 T1 20150130; US 2010147423 A1 20100617; US 9328405 B2 20160503; ZA 200908581 B 20100825

DOCDB simple family (application)
EP 09450220 A 20091123; AT 19042008 A 20081205; AU 2009240807 A 20091124; BR PI0905064 A 20091203; CA 2686594 A 20091127; ES 09450220 T 20091123; PL 09450220 T 20091123; SI 200931096 T 20091123; US 62508409 A 20091124; ZA 200908581 A 20091203