

Title (en)  
DISCHARGING CRYOGEN ONTO WORK SURFACES IN A COLD ROLL MILL

Title (de)  
ABFÜHREN VON KRYOGEN AUF ARBEITSFLÄCHEN IN EINEM KALTWALZWERK

Title (fr)  
ÉCOULEMENT DE CRYOGÈNE SUR DES SURFACES DE PIÈCES À TRAVAILLER DANS UN LAMINOIR À FROID

Publication  
**EP 2197600 A1 20100623 (EN)**

Application  
**EP 08828456 A 20080827**

Priority  
• US 2008074451 W 20080827  
• US 96847907 P 20070828

Abstract (en)  
[origin: WO2009029659A1] The present invention is directed to a method and apparatus for adjusting the amount of cryogen delivered to a mill stand (1 ) using a non-optical sensor (16a) to measure at least one operating parameter selected from the group consisting of roll stand parameters, rolled product parameters, and cryogen parameters. Output signals, are generated by the non-optical sensor and a controller (17) calculates numeric values based on the signals. When the calculated numeric values reach a predetermined set point value that correlates with mill stand temperature, the flow of cryogen is adjusted to disperse a desired amount of cryogenic fluid to said mill stand (1 ) to control rolling temperature.

IPC 8 full level  
**B21B 27/06** (2006.01); **B21B 27/10** (2006.01); **B21B 37/74** (2006.01); **B21B 45/02** (2006.01)

CPC (source: EP US)  
**B08B 3/022** (2013.01 - EP US); **B08B 5/026** (2013.01 - EP US); **B21B 27/10** (2013.01 - EP US); **B21B 37/74** (2013.01 - EP US); **B21B 45/0209** (2013.01 - EP US); **B21B 38/006** (2013.01 - EP US)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)  
AL BA MK RS

DOCDB simple family (publication)  
**WO 2009029659 A1 20090305**; BR PI0815930 A2 20150929; CA 2697841 A1 20090305; CN 101842172 A 20100922; EP 2197600 A1 20100623; EP 2197600 A4 20111005; MX 2010002066 A 20100315; US 2012000213 A1 20120105

DOCDB simple family (application)  
**US 2008074451 W 20080827**; BR PI0815930 A 20080827; CA 2697841 A 20080827; CN 200880113546 A 20080827; EP 08828456 A 20080827; MX 2010002066 A 20080827; US 67526608 A 20080827