

Title (en)

Method for producing the sealing seat with injection holes of a fuel injector

Title (de)

Verfahren zur Herstellung des Dichtungssitzes mit Einspritzlöchern für eine Kraftstoffeinspritzdüse

Title (fr)

Procédé de fabrication d'un siège de scellement avec des trous d'injection d'un injecteur de carburant

Publication

EP 2199593 B1 20110615 (EN)

Application

EP 08425800 A 20081217

Priority

EP 08425800 A 20081217

Abstract (en)

[origin: EP2199593A1] Method for producing the sealing seat (11) of a fuel injector (1) for an internal-combustion engine, the sealing seat (11) having a plurality of injection holes (3); the method comprises the steps of: mixing plastic binder with a powdered metal so as to obtain a homogeneous compound; injecting, in order to form the sealing seat (11), the homogeneous compound into a mould (14) that reproduces in negative the shape of the sealing seat (11); obtaining within the mould (14) a plurality of punches (15) that reproduce in negative at least partially the shape of the injection holes (3) in such a way as to form within the mould (14) the sealing seat (11), which already presents the injection holes (3); and subjecting the sealing seat (11) to a thermal treatment to eliminate the plastic binder and sinter the powdered metal.

IPC 8 full level

F02M 61/16 (2006.01); **F02M 61/18** (2006.01)

CPC (source: EP)

F02M 61/168 (2013.01); **F02M 61/1806** (2013.01)

Cited by

EA019822B1

Designated contracting state (EPC)

DE FR IT

DOCDB simple family (publication)

EP 2199593 A1 20100623; **EP 2199593 B1 20110615**

DOCDB simple family (application)

EP 08425800 A 20081217