

Title (en)

POSITION DETECTION DEVICE AND METHOD FOR DETECTING AT LEAST TWO POSITIONS

Title (de)

POSITIONSERFASSUNGSVORRICHTUNG UND VERFAHREN ZUR ERFASSUNG VON MINDESTENS ZWEI POSITIONEN

Title (fr)

DISPOSITIF DE DÉTECTION DE POSITIONS ET PROCÉDÉ POUR DÉTECTER AU MOINS DEUX POSITIONS

Publication

EP 2200513 A2 20100630 (DE)

Application

EP 08802257 A 20080916

Priority

- EP 2008007728 W 20080916
- DE 102007045189 A 20070921

Abstract (en)

[origin: WO2009040026A2] The invention relates to a position detection device for detecting at least a first and a second position of a syringe die relative to the syringe body of a syringe, comprising at least three switching devices, wherein at least one switching device is configured as a reed contact, and at least one switching device is configured as a magnet.

IPC 8 full level

A61B 5/15 (2006.01)

CPC (source: EP)

A61M 5/1452 (2013.01); **A61B 5/028** (2013.01); **A61M 5/1684** (2013.01); **A61M 5/1685** (2013.01); **A61M 5/31505** (2013.01); **A61M 5/31548** (2013.01); **A61M 5/31561** (2013.01); **A61M 5/31563** (2013.01); **A61M 5/31591** (2013.01); **A61M 2005/31508** (2013.01); **A61M 2205/3382** (2013.01); **A61M 2205/3386** (2013.01)

Citation (search report)

See references of WO 2009040026A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

WO 2009040026 A2 20090402; **WO 2009040026 A3 20090917**; CA 2700289 A1 20090402; CN 101868179 A 20101020; DE 102007045189 A1 20090409; DE 202007018843 U1 20091001; EP 2200513 A2 20100630

DOCDB simple family (application)

EP 2008007728 W 20080916; CA 2700289 A 20080916; CN 200880116114 A 20080916; DE 102007045189 A 20070921; DE 202007018843 U 20070921; EP 08802257 A 20080916