

Title (en)

GLOW PLUG HAVING COKING-OPTIMIZED DESIGN

Title (de)

GLÜHKERZE MIT VERKOKUNGSOPTIMIERTEM DESIGN

Title (fr)

BOUGIE DE PRÉCHAUFFAGE DU TYPE OPTIMISÉ EN RÉDUCTION DE COKÉFACTION

Publication

EP 2201298 A2 20100630 (DE)

Application

EP 08801195 A 20080821

Priority

- DE 2008001372 W 20080821
- DE 102007044967 A 20070919

Abstract (en)

[origin: WO2009036724A2] The invention relates to a glow plug, in particular for operation in an internal combustion engine, comprising at least one heating rod (1) and at least one body (2), and further comprising at least one annular gap (3) disposed between the heating rod (1) and the body (2), and at least one space (4) disposed substantially between the heating rod (1) and the body (2).

IPC 8 full level

F23Q 7/00 (2006.01)

CPC (source: EP US)

F23Q 7/001 (2013.01 - EP US)

Citation (search report)

See references of WO 2009036724A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

WO 2009036724 A2 20090326; WO 2009036724 A3 20090611; CN 101828076 A 20100908; DE 102007044967 A1 20090402; EP 2201298 A2 20100630; EP 2201298 B1 20150304; KR 20100069654 A 20100624; RU 2010115078 A 20111027; RU 2480676 C2 20130427; US 2010236512 A1 20100923; US 8479697 B2 20130709

DOCDB simple family (application)

DE 2008001372 W 20080821; CN 200880108407 A 20080821; DE 102007044967 A 20070919; EP 08801195 A 20080821; KR 20107006347 A 20080821; RU 2010115078 A 20080821; US 67873608 A 20080821