

Title (en)  
OPERATING METHOD FOR A COOLING SECTION HAVING CENTRALIZED DETECTION OF VALVE CHARACTERISTICS AND OBJECTS CORRESPONDING THERETO

Title (de)  
BETRIEBSVERFAHREN FÜR EINE KÜHLSTRECKE MIT ZENTRALISierter ERFASSUNG VON VENTILCHARAKTERISTIKEN UND HIERMIT KORRESPONDIERENDE GEGENSTÄNDE

Title (fr)  
PROCÉDÉ DE FONCTIONNEMENT D'UN CIRCUIT DE REFROIDISSEMENT À SAISIE CENTRALISÉE DE CARACTÉRISTIQUES DE VANNES ET OBJETS CORRESPONDANTS

Publication  
**EP 2203263 B1 20121121 (DE)**

Application  
**EP 08803522 A 20080902**

Priority  
• EP 2008061551 W 20080902  
• DE 102007046279 A 20070927

Abstract (en)  
[origin: WO2009043668A1] The invention relates to a cooling section having a plurality of coolant outlets (2), by means of which a coolant (4) can be applied to a rolling stock (3) passing through the cooling section (1) during the normal operation of the cooling section (1). The coolant outlets (2) are supplied with the coolant (4) via transmission lines (5) and a mutual main line (6), which the transmission lines (5) have in common. Individually opening and closing valves (7) are disposed in the transmission lines (5) such that the supply of coolant (4) to the coolant outlets (2) can be produced and interrupted by transmission line. An automation device (8) of the cooling section (1) opens and closes the valves (7) at valve-specific opening times and at valve-specific closing times during the normal operation of the cooling section (1) in order to apply coolant (4) to the rolling stock (3) in accordance with a quantitative target coolant course. During the determination of the valve-specific opening times, said automation device takes into consideration a respective valve-specific characteristic. In calibration operation of the cooling section (1), the respective valve-specific characteristic is initially determined at least for some of the valves (7) by opening and closing the respective valve (7), and detecting the chronological course of the quantitative coolant flow (Q) effected thereby by means of a measuring arrangement (12) disposed in the main line (6).

IPC 8 full level  
**B21B 45/02** (2006.01)

CPC (source: EP US)  
**B21B 45/0218** (2013.01 - EP US); **C21D 9/573** (2013.01 - EP US); **C21D 11/005** (2013.01 - EP US); **B21B 37/76** (2013.01 - EP US); **B21B 38/00** (2013.01 - EP US); **B21B 45/0233** (2013.01 - EP US); **C21D 1/667** (2013.01 - EP US); **Y10T 137/0318** (2015.04 - EP US); **Y10T 137/0324** (2015.04 - EP US); **Y10T 137/0363** (2015.04 - EP US); **Y10T 137/877** (2015.04 - EP US); **Y10T 137/87925** (2015.04 - EP US)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**DE 102007046279 A1 20090409**; BR PI0817573 A2 20150818; CN 101952059 A 20110119; CN 101952059 B 20130619; EP 2203263 A1 20100707; EP 2203263 B1 20121121; PL 2203263 T3 20130430; RU 2010116413 A 20111110; RU 2479369 C2 20130420; UA 99306 C2 20120810; US 2010312399 A1 20101209; US 8463446 B2 20130611; WO 2009043668 A1 20090409; WO 2009043668 A8 20090528

DOCDB simple family (application)  
**DE 102007046279 A 20070927**; BR PI0817573 A 20080902; CN 200880109646 A 20080902; EP 08803522 A 20080902; EP 2008061551 W 20080902; PL 08803522 T 20080902; RU 2010116413 A 20080902; UA A201003541 A 20080902; US 67998108 A 20080902