

Title (en)  
Detent fitting and pull-out design

Title (de)  
Rastbeschlag und Auszugsführung

Title (fr)  
Ferrure à cran d'arrêt et guidage d'extraction

Publication  
**EP 2208440 B1 20131106 (DE)**

Application  
**EP 10150865 A 20100115**

Priority  
• DE 202009000037 U 20090119  
• DE 202009001516 U 20090206

Abstract (en)  
[origin: EP2208440A1] The detent fitting has a switching element (10) which is moveable along a switching curve (20). The switching element is latched in a closed position on the switching curve and is prestressed in the latched position by a spring. A junction is provided on the switching curve for the switching element and a one-side working pawl (40) is arranged on the junction. An independent claim is also included for a pull-out guide with a guide rail.

IPC 8 full level  
**A47B 88/04** (2006.01)

CPC (source: EP)  
**A47B 88/463** (2016.12)

Cited by  
CN107105896A; CN109475229A; EP2807951A3; CN104207507A; CN105658113A; EP3266347A1; US2015097473A1; CN104427908A;  
EP3009046A1; US9295329B2; CN113367493A; US10051962B2; WO2015058222A1; WO2018011355A1; WO2018011354A1; US10172461B2;  
DE102018105116A1; WO2019170619A1; WO2024039308A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)  
**EP 2208440 A1 20100721; EP 2208440 B1 20131106**; DE 202009001516 U1 20100624

DOCDB simple family (application)  
**EP 10150865 A 20100115**; DE 202009001516 U 20090206