

Title (en)
High security lock cylinder with pre-determined breaking line

Title (de)
Hochsicherheitsschließzylinder mit im Voraus bestimmter Abschaltlinie

Title (fr)
Cylindre de verrouillage haute sécurité avec ligne de rupture prédéterminée

Publication
EP 2208839 A1 20100721 (EN)

Application
EP 09150679 A 20090115

Priority
EP 09150679 A 20090115

Abstract (en)
The present invention proposes a lock cylinder conventionally having two cylinder halves with respective cylinder cores and housings accommodating core pins and housing pins for sensing a key inserted into the key slot within said cylinder core. The lock cylinder core's pins being conventionally aligned to allow rotation of the plug to effect locking and unlocking by a correct key, said core pins are spring tensioned by respective housing pins. The outer half-cylinder according to the present invention is arranged in the form of an outer part and a longitudinally longer inner part the connection between those parts being mechanically weakened and therefore firstly breakable in response to twisting forces applied by the periphery of outermost surface of said outer part.

IPC 8 full level
E05B 17/00 (2006.01); **E05B 27/00** (2006.01)

CPC (source: EP)
E05B 9/041 (2013.01); **E05B 17/0062** (2013.01)

Citation (search report)

- [X] AT 8244 U1 20060415 - KABA GMBH [AT]
- [X] DE 2822132 A1 19791122 - KARRENBERG FA WILHELM
- [X] DE 29808432 U1 19980730 - AUGUST KNAPP SCHLIESTECHNIK GM [DE]
- [X] DE 20021352 U1 20010322 - WINKHAUS FA AUGUST [DE]
- [EX] WO 2009055881 A1 20090507 - MAUER LOCKING SYSTEMS LTD [BG], et al

Cited by
EP3150783A1; CN102605999A; ES2400555A1; GB2545389A; GB2545389B; ITTO20130761A1; EP2722470A1; WO2013005039A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
EP 2208839 A1 20100721

DOCDB simple family (application)
EP 09150679 A 20090115