

Title (en)

YAW RATE SENSOR HAVING TWO SENSITIVE AXES

Title (de)

DREHRATENSENSOR MIT ZWEI SENSITIVEN ACHSEN

Title (fr)

CAPTEUR DE VITESSE DE ROTATION À DEUX AXES SENSIBLES

Publication

EP 2210060 A1 20100728 (DE)

Application

EP 07822375 A 20071108

Priority

EP 2007062073 W 20071108

Abstract (en)

[origin: WO2009059639A1] The invention relates to a yaw rate sensor, comprising a substrate (10), a bearing (20), an oscillating structure (40), which by means of springs (30) is rotatably suspended on the bearing (20) in order to perform a planar driving oscillating movement, and drive means for producing a planar driving oscillating movement of the oscillating structure (40). The essence of the invention is that the yaw rate sensor comprises first evaluation means for detecting a rotation in a first rotational axis and second evaluation means for detecting a rotation in a second rotational axis.

IPC 8 full level

G01C 19/56 (2012.01)

CPC (source: EP US)

G01C 19/5712 (2013.01 - EP US)

Citation (search report)

See references of WO 2009059639A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

WO 2009059639 A1 20090514; CN 101855515 A 20101006; EP 2210060 A1 20100728; JP 2011503557 A 20110127; KR 20100080555 A 20100708; US 2011088469 A1 20110421

DOCDB simple family (application)

EP 2007062073 W 20071108; CN 200780101448 A 20071108; EP 07822375 A 20071108; JP 2010532443 A 20071108; KR 20107010148 A 20071108; US 51383407 A 20071108