

Title (en)

Method for applying a viscous, hardening coating mass

Title (de)

Verfahren zum Auftragen einer viskosen, aushärtenden Beschichtungsmasse

Title (fr)

Procédé d'application d'une masse de revêtement visqueuse durcissante

Publication

EP 2216463 B1 20160106 (DE)

Application

EP 10152703 A 20100204

Priority

DE 102009007913 A 20090206

Abstract (en)

[origin: EP2216463A2] The method involves applying a layer of coating mass on a subsurface for formation of a bonding course, and applying another layer of coating mass on the former layer of coating mass for forming an armoring layer, such that the total thickness of the layers arranged one after another amounts to 1 mm. Pressure required for application of the coating mass is produced by a pump, and the former layer is produced by a nozzle that has an opening with diameter of 0.4 to 0.6 mm, where the pump is driven by an internal combustion engine. An independent claim is also included for a coating system for forming a plaster layer of a facade system.

IPC 8 full level

E04F 21/12 (2006.01)

CPC (source: EP)

E04F 21/12 (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

EP 2216463 A2 20100811; EP 2216463 A3 20120425; EP 2216463 B1 20160106; DE 102009007913 A1 20100819;
DE 102009007913 A9 20101202

DOCDB simple family (application)

EP 10152703 A 20100204; DE 102009007913 A 20090206