

Title (en)

INPUT/OUTPUT SIGNAL CONTROLLER

Title (de)

REGLER FÜR EIN-/AUSGANGSSIGNAL

Title (fr)

CONTRÔLEUR DE SIGNAL D'ENTRÉE/SORTIE

Publication

EP 2216949 A1 20100811 (EN)

Application

EP 08791159 A 20080715

Priority

- JP 2008062734 W 20080715
- JP 2008118665 A 20080430

Abstract (en)

To easily judge a transmission signal outputted from an own electronic device. A transmission part 7 outputs a transmission signal to a transmission path 1 side. Switching parts Q1 and Q2 are connected between a constant voltage power source and the transmission path 1, to switch on/off of a signal supplied from the constant voltage power source, being the transmission signal from the transmission part 7, and output it to the transmission path 1. A reception part 9 receives the transmission signal from the transmission path 1. A detection part 13 is connected between the constant voltage power source and the switching parts Q1, Q2, to detect the transmission signal from the transmission part 7 flowing through the switching parts Q1 and Q2. A selection part 15 selects the reception part 9 , when the transmission signal from the transmission part 7 is not detected by the detection part 13.

IPC 8 full level

H04L 25/02 (2006.01)

CPC (source: EP US)

H03K 19/018592 (2013.01 - EP US); **H04L 5/1415** (2013.01 - EP US); **H04L 25/0298** (2013.01 - EP US); **H04B 2203/5445** (2013.01 - EP US);
H04B 2203/547 (2013.01 - EP US); **H04L 25/0272** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

EP 2216949 A1 20100811; EP 2216949 A4 20120829; EP 2216949 B1 20150422; JP 4589462 B2 20101201; JP WO2009133633 A1 20110825;
US 2010277217 A1 20101104; US 7911232 B2 20110322; WO 2009133633 A1 20091105

DOCDB simple family (application)

EP 08791159 A 20080715; JP 2008062734 W 20080715; JP 2010509993 A 20080715; US 81177108 A 20080715