

Title (en)
Needle for a textile machine

Title (de)
Nadel für eine Textilmaschine

Title (fr)
Aiguille pour une machine textile

Publication
EP 2218812 A1 20100818 (DE)

Application
EP 09152725 A 20090212

Priority
EP 09152725 A 20090212

Abstract (en)

The needle is a felting- or forked-needle. The tipped working section (17) is connected to a lower shaft (20). This continues to an upper shaft section (25). All sections extend longitudinally and coaxially. The top of the needle (30) includes a retention section (32). In novel design, this has two limbs (38, 39) which extend away from each other and transversely with respect to the needle axis (16). The retention section is symmetrical about a notional plane extending along the axis. The plane lies at right angles to the limb extensions. On top of the retention section, a contact area (for penetrating force transmission) runs transversely along its entire length. The circular shaft sections and the retention section have constant cross sections along their respective lengths. The retention section width is less than the diameter of the upper shaft section. In a variant design, the cross section of the retention section departs from circular, being oval, elliptical, polygonal, rectangular, triangular or hexagonal. Its corners and/or edges are rounded. The upper shaft cross section is optionally non-circular. The area of the upper shaft section corresponds with that of the lower shaft section. The upper shaft section has uniformly-distributed lines of contact, lying on a common notional cylindrical surface about the longitudinal axis. These lines spiral along this cylindrical surface. A textile machine is equipped with the needles, spaced-apart and held in parallel grooves with penetrating bores through which the shafts pass. The needle holding sections extend away from the needle axes, held in and projecting along the grooves in the needle beam.

Abstract (de)

Die Erfindung betrifft eine Nadel (15) für eine Textilmaschine, insbesondere eine Filznadel oder eine Gabelnadel. Ein Arbeitsabschnitt (17) erstreckt sich entlang einer Längsachse (16) und weist eine Nadelspitze (18) auf. An den Arbeitsabschnitt (17) schließen sich ein unterer Schaftabschnitt (20) und ein oberer Schaftabschnitt (25) an, die beide koaxial zueinander entlang der Längsachse (16) angeordnet sind. Anschließend an den oberen Schaftabschnitt (25) ist ein Nadelfuß(30) vorgesehen, der einen Haltemittel (32) aufweist. Das Haltemittels (32) erstreckt sich in einer Querrichtung (31) und weist zwei ausgehend von der Längsachse (16) voneinander weg ragende Schenkel (38,39) auf.

IPC 8 full level

D04H 18/02 (2012.01)

CPC (source: EP US)

D04H 18/02 (2013.01 - EP US)

Citation (applicant)

US 2857650 A 19581028 - LAUTERBACH HERBERT G

Citation (search report)

- [X] DE 3105358 A1 19820909 - DILO KG MASCHF OSKAR [DE]
- [A] DE 2108115 A1 19710923
- [A] US 2663065 A 19531222 - THOMAS DINHAM ALFRED
- [A] DE 1410492 A1 19681024 - DU PONT
- [A] DE 6606717 U 19701112 - SINGER CO [US]
- [X] REICHELT W: "MODERNE FILZNADELN ZUR ERZEUGUNG MARKTGERECHTER VLISSSTOFFE", MELLIAND TEXTILBERICHTE, DEUTSCHER FACHVERLAG, FRANKFURT AM MAIN, DE, vol. 73, no. 5, 1 May 1992 (1992-05-01), pages 386 - 390, XP000273203, ISSN: 0341-0781

Cited by

CN112030373A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA RS

DOCDB simple family (publication)

EP 2218812 A1 20100818; EP 2218812 B1 20110316; CN 101805960 A 20100818; CN 101805960 B 20120222;
DE 502009000460 D1 20110428; ES 2362978 T3 20110718; JP 2010209506 A 20100924; JP 5697815 B2 20150408;
KR 101182119 B1 20120913; KR 20100092380 A 20100820; TW 201040344 A 20101116; TW I435966 B 20140501;
US 2010251525 A1 20101007; US 8245372 B2 20120821

DOCDB simple family (application)

EP 09152725 A 20090212; CN 201010118608 A 20100212; DE 502009000460 T 20090212; ES 09152725 T 20090212;
JP 2010027012 A 20100209; KR 20100012281 A 20100210; TW 99104254 A 20100211; US 70464010 A 20100212