

Title (en)
FLUSH CONTROL ASSEMBLY

Title (de)
SPÜLUNGSSTEUERANORDNUNG

Title (fr)
DISPOSITIF DE COMMANDE POUR CHASSE D'EAU

Publication
EP 2220300 A1 20100825 (EN)

Application
EP 08845952 A 20081031

Priority
• GB 2008003690 W 20081031
• GB 0721456 A 20071101

Abstract (en)
[origin: GB2454222A] The invention relates to a toilet flush control assembly 10 connected to an upper part of a siphon (56 figure 7) of a toilet so as to connect the interior of the siphon to atmosphere via the assembly 10 to provide a variable flush facility. The assembly comprises a body (22 figure 4) and a hollow connection (12 figure 2) in the form of a short hollow pipe extending from the body (22 figure 4). The body comprises a base section (24 figure 4) with side walls (26 figure 6). A closure member (40 figure 4) in the form of a disc is rotatably mounted to the body (22 figure 4) so as to be movable with respect to an end opening of the connection member (12 figure 2). The closure member (40 figure 4) comprises one or more differently sized openings (50 figure 4) which align with the end opening of the connection projection (12 figure 2) as the closure member (40 figure 4) is rotated. The amount of water used during a flush cycle may be reduced by selecting one of the larger sized openings (50 figure 4), which allows a greater amount of air to enter the siphon (56 figure 7) during a flush cycle.

IPC 8 full level
E03D 1/14 (2006.01); **F16K 3/08** (2006.01)

CPC (source: EP GB)
E03D 1/14 (2013.01 - GB); **E03D 1/141** (2013.01 - EP); **F16K 3/085** (2013.01 - EP)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA MK RS

DOCDB simple family (publication)
GB 0721456 D0 20071212; **GB 2454222 A 20090506**; **GB 2454222 B 20100630**; EP 2220300 A1 20100825; WO 2009056846 A1 20090507

DOCDB simple family (application)
GB 0721456 A 20071101; EP 08845952 A 20081031; GB 2008003690 W 20081031