

Title (en)

METHOD FOR COATING A MOLDED FIBER CEMENT ARTICLE OR MOLDED CONCRETE ARTICLE

Title (de)

VERFAHREN ZUM BESCHICHTEN EINES FASERZEMENT- ODER BETON-FORMTEILS

Title (fr)

PROCÉDÉ D'APPLICATION D'UN REVÊTEMENT SUR UNE PIÈCE MOULÉE EN BÉTON OU EN FIBROCIMENT

Publication

EP 2222467 A1 20100901 (DE)

Application

EP 08861798 A 20081219

Priority

- EP 2008067961 W 20081219
- EP 07123661 A 20071219
- EP 08861798 A 20081219

Abstract (en)

[origin: WO2009077612A1] The invention relates to a method for coating a molded fiber cement article or molded concrete article, characterized by a) arranging and securing the molded article in a die, the plastic film being applied between the wall of the die and the molded article, b) evacuating the air from the chamber between the plastic film and the molded article, c) heating the plastic film, d) using ambient air to relieve a second chamber between the plastic film and the wall of the die to atmospheric pressure, and e) thereby pressing the plastic film onto the molded article and while maintaining a vacuum during this pressing step. The invention also relates to molded fiber cement articles or molded concrete articles.

IPC 8 full level

B32B 37/10 (2006.01); **B29C 51/10** (2006.01); **B29C 63/02** (2006.01); **E04F 13/18** (2006.01)

CPC (source: EP US)

B29C 51/16 (2013.01 - EP US); **B29C 63/02** (2013.01 - EP US); **B29C 2043/561** (2013.01 - EP US); **B29C 2791/006** (2013.01 - EP US); **B29K 2709/06** (2013.01 - EP US); **B29L 2031/10** (2013.01 - EP US); **B29L 2031/104** (2013.01 - EP US); **Y10T 428/29** (2015.01 - EP US)

Citation (search report)

See references of WO 2009077612A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA MK RS

DOCDB simple family (publication)

WO 2009077612 A1 20090625; EP 2222467 A1 20100901; US 2010272992 A1 20101028

DOCDB simple family (application)

EP 2008067961 W 20081219; EP 08861798 A 20081219; US 80968008 A 20081219