

Title (en)
PNEUMATIC TIRE

Title (de)
LUFTREIFEN

Title (fr)
PNEU

Publication
EP 2223812 A1 20100901 (EN)

Application
EP 08854137 A 20081125

Priority

- JP 2008071329 W 20081125
- JP 2007307703 A 20071128
- JP 2007307704 A 20071128
- JP 2007309157 A 20071129

Abstract (en)
To improve the steering stability on a wet road surface. A land ratio of a shoulder portion sh of a tread portion 2 is 57 to 72%, and a land ratio of a center portion Ce is 40 to 55%. In the center portion Ce, one row block made up of center blocks 6 is formed. Each of the center blocks 6 has its width gradually reduced from a position establishing an axial maximum width BW toward both a leading end and a trailing end relative to the tire rotating direction, each of the center blocks being provided with, at the leading end thereof, a tip portion 6a that sharpens toward the leading end, and being provided with, at the trailing end thereof, a concave portion 6b that smoothly concaves toward the leading end. In each of the center blocks 6, a ratio (BL/BW) between the axial maximum width BW and a maximum length BL in the circumferential direction is 1.00 to 1.20.

IPC 8 full level
B60C 11/03 (2006.01); **B60C 11/01** (2006.01); **B60C 11/04** (2006.01); **B60C 11/11** (2006.01); **B60C 11/13** (2006.01)

CPC (source: EP US)
B60C 11/03 (2013.01 - US); **B60C 11/0311** (2013.01 - EP US); **B60C 11/033** (2013.01 - EP US); **B60C 11/11** (2013.01 - EP US)

Cited by
EP3730315A1; EP2777950A3

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA MK RS

DOCDB simple family (publication)
EP 2223812 A1 20100901; **EP 2223812 A4 20110105**; **EP 2223812 B1 20120627**; CN 101878120 A 20101103; CN 101878120 B 20120926; US 2010300588 A1 20101202; US 2013263987 A1 20131010; US 2013269847 A1 20131017; US 8474497 B2 20130702; WO 2009069585 A1 20090604

DOCDB simple family (application)
EP 08854137 A 20081125; CN 200880118414 A 20081125; JP 2008071329 W 20081125; US 201313909768 A 20130604; US 201313909862 A 20130604; US 74518408 A 20081125