Title (en)
   A COUPLING DEVICE

Title (de)
   VERBINDUNGSVORRICHTUNG

Title (fr)
   DISPOSITIF DE COUPLAGE

Publication
   EP 2231979 B1 20170125 (EN)

Application
   EP 07846452 A 20071219

Priority
   DK 2007050192 W 20071219

Abstract (en)
   [origin: WO2009076952A1] A coupling device connects an operator chain of a chain operator to a sash member (1) of a window. The coupling device comprises a securing means (10) adapted to be secured to said sash member (1), a first coupling member (3), which at a first end is designed for connection with said free end of said operator means (2) and at a second end has a mouth (5a) of a cut-out (5), and a second coupling member (6) comprising a shaft member (6a) rotationally secured to said securing means (10). Said shaft member (6a) comprises a connection section (8) with a first transverse dimension (a) corresponding to a width of said mouth (5a) and a second, larger dimension (b) corresponding to a width of said cut-out (5), and rotating means (7) for rotating said shaft member (6a). The coupling device further comprises an indicating means (11) secured to said securing means (10) and abutting said shaft member (6a) such as to indicate to a user, by operation of said rotating means (7), the rotational position of said shaft member (6a).

IPC 8 full level
   E05F 11/06 (2006.01); **E05F 15/619** (2015.01)

CPC (source: EP)
   E05F 11/06 (2013.01); **E05F 15/619** (2015.01); E04D 13/035 (2013.01); E05Y 2201/214 (2013.01); E05Y 2201/656 (2013.01); E05Y 2201/724 (2013.01); E05Y 2900/148 (2013.01); E05Y 2900/154 (2013.01)

Designated contracting state (EPC)
   AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
   WO 2009076952 A1 20090625; CN 101821469 A 20100901; CN 101821469 B 20130710; EP 2231979 A1 20100929; EP 2231979 B1 20170125; PL 2231979 T3 20170731

DOCDB simple family (application)
   DK 2007050192 W 20071219; CN 200780101102 A 20071219; EP 07846452 A 20071219; PL 07846452 T 20071219