

Title (en)

METHOD FOR PRODUCING A BREAK IN A CHASSIS SECTION OF A MOTOR VEHICLE AS NECESSARY

Title (de)

VERFAHREN ZUM BEDARFSWEISEN ERZEUGEN EINES DURCHBRUCHS IN EINEM KAROSSERIEABSCHNITT EINES FAHRZEUGS

Title (fr)

PROCÉDÉ POUR MÉNAGER UN PASSAGE DANS UNE SECTION DE CARROSSERIE D'UN VÉHICULE EN FONCTION DES BESOINS

Publication

EP 2240288 A2 20101020 (DE)

Application

EP 09705251 A 20090130

Priority

- EP 2009000630 W 20090130
- DE 102008007284 A 20080202

Abstract (en)

[origin: WO2009095262A2] In a method according to the invention to produce breaks in a chassis section (1) of a motor vehicle as necessary, at least two guide holes (5) are provided which correspond to the necessary breaks (3) in the chassis section (1) as the case requires. Depending on what break (3) is actually required in the affected vehicle chassis, one or the other guide hole (5) is used for introduction of a tool (10). The tool (10) comprises a tension stamp (12) with a stamp plate (14) and a tension rod (16). The tension rod (16) is passed through the respective guide hole (5) from the back side (R) of the chassis section (1) and is introduced into a drive unit (30) placed at the front side of the chassis section (1). The drive unit (30) is designed as a hydraulic piston-cylinder unit, for example, and has a matrix-like free end section (36) at the side facing the chassis section (1), said end section forming a stamping apparatus together with the stamping plate (14). The drive unit (30) moves the stamping plate (14) and the end section (36) together in such a way that the panel section (6) lying therebetween is cut away, thus resulting in the necessary break (3). With the method according to the invention, preparation areas can be provided with comparatively very small guide holes (5) into which the tool (10) is inserted at an already painted chassis as necessary and subsequently the necessary breaks (3) are produced depending on the vehicle configuration. The un-necessary guide holes (5) can be sealed with small plugs.

IPC 8 full level

B21D 28/26 (2006.01); **B21D 28/34** (2006.01)

CPC (source: EP)

B21D 28/26 (2013.01); **B21D 28/343** (2013.01); **B21D 53/88** (2013.01)

Citation (search report)

See references of WO 2009095262A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

DE 102008007284 A1 20090806; AT E512735 T1 20110715; EP 2240288 A2 20101020; EP 2240288 B1 20110615; WO 2009095262 A2 20090806; WO 2009095262 A3 20100121

DOCDB simple family (application)

DE 102008007284 A 20080202; AT 09705251 T 20090130; EP 09705251 A 20090130; EP 2009000630 W 20090130