

Title (en)

Points for transport device, in particular suspended transport device

Title (de)

Weiche für eine Fördereinrichtung, insbesondere Hängefördereinrichtung

Title (fr)

Aiguillage pour un dispositif de transport, notamment dispositif de transport suspendu

Publication

EP 2241673 B1 20160518 (DE)

Application

EP 10155933 A 20100309

Priority

DE 102009017882 A 20090417

Abstract (en)

[origin: EP2241673A2] The deflector has a switch blade (20) arranged at a frame and switchable between switching positions. A switching device has a switching operation element (32) and a slotted lever gear (30) that has a slotted lever element (34). The blade and the lever element are connected with one another by a slotted lever pin (42) and a slotted lever guide channel (36). The pin and the channel stay in engagement with one another, such that the gear changes a switching movement of the lever element into a movement of the blade, and locks the blade in the defined switching position.

IPC 8 full level

E01B 25/26 (2006.01)

CPC (source: EP)

E01B 25/26 (2013.01)

Cited by

US11723372B2; IT201600113860A1; CN108360312A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

EP 2241673 A2 20101020; EP 2241673 A3 20150624; EP 2241673 B1 20160518; DE 102009017882 A1 20101021;
DE 102009017882 B4 20190814

DOCDB simple family (application)

EP 10155933 A 20100309; DE 102009017882 A 20090417