

Title (en)
Device for hardening rails

Title (de)
Einrichtung zum Härteln von Schienen

Title (fr)
Dispositif de durcissement de rails

Publication
EP 2243566 A1 20101027 (DE)

Application
EP 10450111 A 20090127

Priority

- EP 09450016 A 20090127
- AT 1752008 A 20080204

Abstract (en)

The device for hardening profiled running rails (1), comprises a cooling means, a transverse displacement means (21) in an area of roller tables, a directing means and a manipulation gripper (3) for bringing the rail in the device, a positioning means (4), a basin and/or a trough with a cooling agent, and a cooling bed (6). The running rails have optional different cross-sectional forms and a length of larger than 50 m by cooling a part of the respective rail cross section over a total rail length in the cooling means. The manipulation gripper is formed from operable pliers. The device for hardening profiled running rails (1), comprises a cooling means, a transverse displacement means (21) in an area of roller tables, a directing means and a manipulation gripper (3) for introducing the rail in the device, a positioning means (4), a basin and/or a trough with a cooling agent, and a cooling bed (6). The running rails have optional different cross-sectional forms and a length of larger than 50 m by cooling a part of the respective rail cross section over a total rail length in the cooling means. The manipulation gripper is formed from identically-shaped, aligned and movably operable pliers, which have homogeneously movable and/or adjustable gripping arms formed with centering parts for an axial alignment of the heads of the rails and with gripper parts for a transversely-aligned holding of rail foots, so that an accurate introduction of the rails is possible in the positioning means and a regulation of the rails is possible in the positioning means. The manipulation gripper is formed with more than two pliers, each of which is 10 m of the basin length. The manipulation gripper and associated bringing means are spatially movable with more than the largest rail height over the roller table and the gripping arms of the pliers are partially lowered between the rollers of the roller tables for receiving the rails in a vertical manner. The positioning means has horizontally aligned retaining components with units for the foot of hangingly introduced rails, which is definable on the units by detachable clamping elements and/or compressor rods distortion-secured in the direction of the rail. The rail is immovably kept by one unit and one detachable clamping element for the rail foot of a component of the positioning means. The remaining units and the clamping elements allow a displacement in the longitudinal direction of the rail. Two basins are horizontally arranged next to each other with positioning means on equal height in an axial-parallel manner. The part of the cooling agent in the basin usable for hardening the rails has a depth, which exceeds 10% the height of the largest rail profile. The basin has a cooling agent inlet on the bottom-side having 1.5 m of the basin length. A regular cooling agent flow is supplyable through the cooling agent inlet. A perforated and flow-throughable plate distanced above the cooling agent inlet is arranged in the basin and/or a nozzle plate assigned in the flow direction of the cooling agent is inserted with channels. A deriving means for the cooling agent is arranged in the basin and/or in supply lines and is openly-adjustable for temporarily emptying the basin. The basin, the units and clamping elements are simultaneously movable in the cooling agent vertically relative to each other in a controlled manner. A vertical holding position and a time period of the basin, the units and clamping elements are adjustable. The units and clamping elements are simultaneously adjustable horizontally transverse to the basin.

Abstract (de)

Die Erfindung betrifft eine Einrichtung zum Härteln von Schienen (1), insbesondere profilierte Fahrschienen, mit gegebenenfalls jeweils unterschiedlicher Querschnittsform und einer Länge von größer als 50m durch Abkühlen von zumindest einem Teil des jeweiligen Schieneneinzelstückes über die gesamte Schienellänge in einem Kühlmittel, bestehend aus Querverschiebemitteln (21) im Bereich eines Rollganges (2), aus Richtmitteln und Manipulationsgreifer (3) zum Verbringen der Schiene (1) in der Einrichtung, mindestens einem Positioniermittel (4), mit jeweils einem Becken (5) bzw. Trog mit Kühlmittel sowie einem Kühlbett (6). Erfundungsgemäß ist vorgesehen, dass das Becken (5) und die Anlagen und die lösbar Spannmittel für den Fuß der hängenden Schiene aller Komponenten des Positioniermittels (4) zur Einbringung der Schiene in das Kühlmittel gleichzeitig vertikal relativ zueinander gesteuert bewegbar und eine jeweilige vertikale Halteposition und Zeitdauer derselben einstellbar sind.

IPC 8 full level

B21B 43/00 (2006.01); **B21B 43/06** (2006.01); **C21D 1/63** (2006.01); **C21D 9/06** (2006.01)

CPC (source: EP KR US)

B21B 43/003 (2013.01 - EP US); **B21B 43/06** (2013.01 - EP US); **C21D 1/18** (2013.01 - KR); **C21D 1/63** (2013.01 - EP US);
C21D 9/0018 (2013.01 - EP US); **C21D 9/04** (2013.01 - EP KR US); **B21B 1/085** (2013.01 - EP US); **B21B 43/00** (2013.01 - EP US);
B21B 43/006 (2013.01 - EP US); **B21B 45/023** (2013.01 - EP US)

Citation (applicant)

AT 410549 B 20030526 - VOEST ALPINE SCHIENEN GMBH & C [AT]

Citation (search report)

- [XAY] EP 1160341 A2 20011205 - VOEST ALPINE SCHIENEN GMBH & C [AT]
- [YDA] AT 410549 B 20030526 - VOEST ALPINE SCHIENEN GMBH & C [AT]
- [A] EP 0441766 A1 19910814 - VOEST ALPINE IND ANLAGEN [AT]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

AT 505930 A4 20090515; AT 505930 B1 20090515; AT E550112 T1 20120415; AT E550113 T1 20120415; AT E554867 T1 20120515;
AU 2009200367 A1 20090820; AU 2009200367 B2 20110331; AU 2011200883 A1 20110324; AU 2011200883 B2 20141204;
AU 2011200892 A1 20110324; AU 2011200892 B2 20140612; AU 2011200893 A1 20110324; AU 2015203117 A1 20150709;
AU 2015203117 B2 20170608; BR 122019018872 B1 20201124; BR 122019018876 B1 20201124; BR 122019018877 B1 20201124;
BR PI0900474 A2 20091110; BR PI0900474 B1 20200211; CA 2652329 A1 20090804; CA 2652329 C 20120327; CA 2742873 A1 20090804;
CA 2742873 C 20130402; CA 2742939 A1 20090804; CA 2742939 C 20130402; CA 2742949 A1 20090804; CA 2742949 C 20130402;
CN 101509060 A 20090819; CN 101509060 B 20110420; CN 102010968 A 20110413; CN 102010968 B 20131106; CN 102010969 A 20110413;
CN 102010969 B 20220603; CN 102010970 A 20110413; CN 102010970 B 20130403; DK 2085160 T3 20120730; DK 2241384 T3 20120709;

DK 2243565 T3 20120709; DK 2243566 T3 20120924; EP 2085160 A1 20090805; EP 2085160 B1 20120425; EP 2241384 A1 20101020; EP 2241384 B1 20120321; EP 2243565 A1 20101027; EP 2243565 B1 20120321; EP 2243566 A1 20101027; EP 2243566 B1 20120627; ES 2382728 T3 20120612; ES 2384441 T3 20120704; ES 2385182 T3 20120719; ES 2386877 T3 20120904; HR P20120492 T1 20120731; HR P20120493 T1 20120731; HR P20120590 T1 20120831; HR P20120750 T1 20121031; JP 2009185385 A 20090820; JP 2012183589 A 20120927; JP 2012184510 A 20120927; JP 2012193455 A 20121011; JP 5163987 B2 20130313; JP 5551734 B2 20140716; JP 5551735 B2 20140716; JP 5551736 B2 20140716; KR 101221567 B1 20130114; KR 20090085544 A 20090807; PL 2085160 T3 20120928; PL 2241384 T3 20120831; PL 2243565 T3 20120831; PL 2243566 T3 20121130; PT 2085160 E 20120621; PT 2241384 E 20120416; PT 2243565 E 20120507; PT 2243566 E 20121002; RU 2388834 C1 20100510; SI 2085160 T1 20120731; SI 2241384 T1 20120531; SI 2243565 T1 20120629; SI 2243566 T1 20121030; TW 200946689 A 20091116; UA 92954 C2 20101227; US 2009200713 A1 20090813; US 2012168043 A1 20120705; US 8226883 B2 20120724; US 8557172 B2 20131015

DOCDB simple family (application)

AT 1752008 A 20080204; AT 09450016 T 20090127; AT 10450109 T 20090127; AT 10450110 T 20090127; AU 2009200367 A 20090202; AU 2011200883 A 20110301; AU 2011200892 A 20110301; AU 2011200893 A 20110301; AU 2015203117 A 20150611; BR 122019018872 A 20090204; BR 122019018876 A 20090204; BR 122019018877 A 20090204; BR P10900474 A 20090204; CA 2652329 A 20090204; CA 2742873 A 20090204; CA 2742939 A 20090204; CA 2742949 A 20090204; CN 200910130734 A 20090204; CN 201010531208 A 20090204; CN 201010531217 A 20090204; CN 201010531221 A 20090204; DK 09450016 T 20090127; DK 10450109 T 20090127; DK 10450110 T 20090127; DK 10450111 T 20090127; EP 09450016 A 20090127; EP 10450109 A 20090127; EP 10450110 A 20090127; EP 10450111 A 20090127; ES 09450016 T 20090127; ES 10450109 T 20090127; ES 10450110 T 20090127; ES 10450111 T 20090127; HR P20120492 T 20120612; HR P20120493 T 20120612; HR P20120590 T 20120713; HR P20120750 T 20120920; JP 2009044817 A 20090204; JP 2012126505 A 20120517; JP 2012126506 A 20120517; JP 2012126507 A 20120517; KR 20090008843 A 20090204; PL 09450016 T 20090127; PL 10450109 T 20090127; PL 10450110 T 20090127; PL 10450111 T 20090127; PT 09450016 T 20090127; PT 10450109 T 20090127; PT 10450110 T 20090127; PT 10450111 T 20090127; RU 2009103537 A 20090203; SI 200930214 T 20090127; SI 200930242 T 20090127; SI 200930265 T 20090127; SI 200930320 T 20090127; TW 98103436 A 20090204; UA A200900814 A 20090204; US 201213415233 A 20120308; US 36487709 A 20090203