

Title (en)
STAND FOR DISPLAYING GOODS, COMPRISING AT LEAST ONE VERTICAL PROP AND PRIMARY SUPPORTS THAT CAN BE SUSPENDED THEREIN

Title (de)
GESTELL ZUR WARENPRÄSENTATION MIT ZUMINDEST EINER VERTIKALSTÜTZE UND DARIN EINHÄNGBAREN PRIMÄRTRÄGERN

Title (fr)
STRUCTURE DE PRÉSENTATION D'ARTICLES COMPORTANT AU MOINS UN MONTANT VERTICAL ET DES SUPPORTS PRIMAIRES

Publication
EP 2244603 B1 20170802 (DE)

Application
EP 08872623 A 20081217

Priority
• CH 2008000540 W 20081217
• DE 202008003362 U 20080223

Abstract (en)
[origin: WO2009103169A1] The stand for displaying goods comprises at least one vertical prop (1) which has a vertically arranged grid of alternating slots (17) and webs (18). Docking elements (21) of primary supports (2) can be suspended in the grid of slots (17) and webs (18) and are intended for directly suspending articles or for holding secondary supports (5). The grid of slots (17) and webs (18) in the vertical prop (1) is arranged in an intermediate web (13) in a mirror-symmetrical manner in two perpendicular lines which are parallel to one another, each line of the grid of slots (17) and webs (18) being delimited by an inner limb (10) and an outer limb (16) which define gaps (12) between them. The two gaps (12) form the access from one front end (19) of the vertical prop (1) to the two grids of slots (17) and webs (18), a free space (15) lying behind the intermediate web (13), facing away from the gaps (12). In a first embodiment, the primary support (2) is equipped with a two-membered docking element (21) having two flanks (211) with at least one hook element (212) each which occupy, in the inserted state, simultaneously slots (17) and webs (18) adjacent beneath it of both lines of the grid of slots (17) and webs (18) of the same vertical prop (1) and project into the free space (15). In a second embodiment, the primary support (2) has a one-membered docking element (21) only, having a flank (211) with at least one hook element (212) and is combined with a secondary support (5) leading to the next primary support (2) having likewise a one-membered, similar docking element (21), the at least one hook element (212) of every one-membered docking element (21) of the two primary supports (2), in the inserted state, in each case occupying only one slot (17) and the web (18) adjacent beneath it of only one line of the grid of slots (17) and webs (18) of a vertical prop (1). The vertical prop (1), in its extension across the hollow space (15), is arranged in a mirror-symmetrical manner towards a second front end (19) with two extended outer limbs (10), an additional intermediate web (13), grids of slots (17) and webs (18) in two parallel perpendicular lines provided therein, and associated inner limbs (16) and gaps (12). In this way, the primary supports (2) can be suspended at the same level via their docking elements (21) from both front ends (19) of the same vertical prop (1).

IPC 8 full level
A47B 57/42 (2006.01); **A47B 96/14** (2006.01); **A47F 5/10** (2006.01)

CPC (source: EP)
A47B 57/42 (2013.01); **A47B 96/1475** (2013.01); **A47F 5/0018** (2013.01); **A47F 5/103** (2013.01)

Cited by
CN108703526A

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)
DE 202008003362 U1 20080515; EP 2244603 A1 20101103; EP 2244603 B1 20170802; JP 2009195677 A 20090903; WO 2009103169 A1 20090827

DOCDB simple family (application)
DE 202008003362 U 20080223; CH 2008000540 W 20081217; EP 08872623 A 20081217; JP 2008245561 A 20080925