

Title (en)

SLOT ANTENNA AND METHOD FOR OPERATING THE SAME

Title (de)

SCHLITZANTENNE UND VERFAHREN ZU IHREM BETRIEB

Title (fr)

ANTENNE À FENTES ET SON PROCÉDÉ D'UTILISATION

Publication

EP 2245704 A1 20101103 (EN)

Application

EP 07870583 A 20071228

Priority

IT 2007000925 W 20071228

Abstract (en)

[origin: WO2009084050A1] A slot antenna having a single -ridge waveguide (13) with a top broadwall (12) and a plurality of radiant elements (5). The radiant elements are formed on the top broadwall (12) and are configured to radiate and receive circularly- polarized waves. Each radiant element (5) is formed by two slots (11) which are arranged at 90 to each other, are non-overlapping, extend on opposite sides with respect of the broadwall axis A and are spaced apart from each other by a mutual distance in the range of $\lambda_{\text{dag}}/4 \pm 20\%$, wherein λ_{dag} is a nominal guide wavelength.

IPC 8 full level

H01Q 21/00 (2006.01); **H01Q 13/10** (2006.01); **H01Q 21/24** (2006.01)

CPC (source: EP)

H01Q 13/10 (2013.01); **H01Q 21/005** (2013.01); **H01Q 21/24** (2013.01)

Citation (search report)

See references of WO 2009084050A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA HR MK RS

DOCDB simple family (publication)

WO 2009084050 A1 20090709; WO 2009084050 A9 20101202; EP 2245704 A1 20101103; EP 2245704 B1 20150218

DOCDB simple family (application)

IT 2007000925 W 20071228; EP 07870583 A 20071228