

Title (en)
SUSCEPTOR WITH CORRUGATED BASE

Title (de)
SUSZEPTOR MIT GEWELLTER BASIS

Title (fr)
SUSCEPTEUR AVEC BASE ONDULÉE

Publication
EP 2250859 B1 20190828 (EN)

Application
EP 08873213 A 20080922

Priority

- US 2008077168 W 20080922
- US 7583708 A 20080314
- US 13757108 P 20080731

Abstract (en)
[origin: WO2009114038A1] A thermally insulated susceptor structure comprises a dimensionally stable corrugated base, a first susceptor, and a second susceptor. At least one of the first susceptor and second susceptor may circumscribe one or more microwave energy transparent areas that allow the transmission of microwave energy through the respective susceptor and/or create localized fields that enhance heating, browning and/or crisping of an adjacent food item.

IPC 8 full level
A23L 5/10 (2016.01); **B65D 81/34** (2006.01); **F24C 7/02** (2006.01); **H05B 6/64** (2006.01); **H05B 6/80** (2006.01)

CPC (source: EP)
B65D 81/3446 (2013.01); **B65D 81/3453** (2013.01); **H05B 6/6494** (2013.01); **B65D 2581/344** (2013.01); **B65D 2581/3472** (2013.01);
B65D 2581/3477 (2013.01); **B65D 2581/3479** (2013.01); **B65D 2581/3493** (2013.01); **B65D 2581/3498** (2013.01)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2009114038 A1 20090917; CA 2718050 A1 20090917; CA 2718050 C 20150623; EP 2250859 A1 20101117; EP 2250859 A4 20140226;
EP 2250859 B1 20190828; ES 2745821 T3 20200303; JP 2011515281 A 20110519; JP 2014053327 A 20140320; JP 5421297 B2 20140219;
JP 5763732 B2 20150812

DOCDB simple family (application)
US 2008077168 W 20080922; CA 2718050 A 20080922; EP 08873213 A 20080922; ES 08873213 T 20080922; JP 2010550660 A 20080922;
JP 2013239595 A 20131120