

Title (en)
Sash bolt-lock

Title (de)
Schließvorrichtung mit Basküleverschluss

Title (fr)
Cremone-serrure

Publication
EP 2253787 A3 20110420 (FR)

Application
EP 10305422 A 20100421

Priority
FR 0952585 A 20090421

Abstract (en)
[origin: EP2253787A2] The lock (1) has a driving mechanism (3) comprising a follower (9) to control a half-turn bolt extended in a front edge (8) of a casing (2) in a projecting locking position. Actuation units (17) activate operation rods (18, 19) respectively extended above and below the casing. A connection rod (20) connects the operation rods through a reversal device when necessary, extends along the edge of the casing in a parallel manner and comprises a slot (21) for passage of the bolt. The casing comprises maintenance and guidance units (29) to maintain and guide a head (13) of the bolt.

IPC 8 full level
E05C 9/02 (2006.01); **E05B 15/16** (2006.01); **E05B 17/00** (2006.01); **E05C 9/00** (2006.01)

CPC (source: EP)
E05C 9/02 (2013.01); **E05B 17/0004** (2013.01); **E05B 2015/1642** (2013.01)

Citation (search report)

- [XY] WO 0159237 A2 20010816 - SARGENT MFG CO [US]
- [XA] US 6068304 A 20000530 - LINDQVIST PER OLOF [SE]
- [YA] US 6767038 B1 20040727 - HUML JAN M [US]
- [A] GB 2444730 A 20080618 - SECURISTYLE LTD [GB]
- [A] US 6637784 B1 20031028 - HAUBER PETER [US], et al

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA ME RS

DOCDB simple family (publication)
FR 2944548 A1 20101022; FR 2944548 B1 20150515; EP 2253787 A2 20101124; EP 2253787 A3 20110420; EP 2253787 B1 20120718

DOCDB simple family (application)
FR 0952585 A 20090421; EP 10305422 A 20100421