

Title (en)

CRUSH RESISTANT CONDUCTOR INSULATION

Title (de)

STAUCHFESTE LEITERISOLIERUNG

Title (fr)

ISOLATION DE CONDUCTEUR RÉSISTANT À L'ÉCRASEMENT

Publication

**EP 2255364 A1 20101201 (EN)**

Application

**EP 09721438 A 20090316**

Priority

- US 2009037213 W 20090316
- US 3705508 P 20080317
- US 3719208 P 20080317

Abstract (en)

[origin: WO2009117331A1] A process of twinning a pair of polymer-insulated conductors to form a twisted pair, where the polymer-insulated conductors are formed by extruding a uniformly thick coating of polymer onto the conductors. More than one twisted pair is encased in a polymer jacket forming a cable. The twisted pair obtains a desirable average impedance performance using a reduced amount by weight of polymer forming said polymer-insulated conductors by: (i) extruding to form longitudinally running peaks and valleys in the exterior surface of each of the polymer-insulated conductors of the pair of polymer-insulated conductors and (ii) twinning resultant polymer-insulated conductors to nest at least one of the peaks in the exterior surface of one of the polymer-insulated conductors in at least one of said valleys in the exterior surface of the other of the polymer-insulated conductors of the pair of polymer-insulated conductors.

IPC 8 full level

**H01B 7/02** (2006.01); **H01B 13/14** (2006.01)

CPC (source: EP)

**H01B 7/0275** (2013.01); **H01B 13/142** (2013.01); **H01B 13/143** (2013.01); **H01B 7/0233** (2013.01)

Citation (search report)

See references of WO 2009117331A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)

AL BA RS

DOCDB simple family (publication)

**WO 2009117331 A1 20090924**; CN 101978433 A 20110216; EP 2255364 A1 20101201; JP 2011514649 A 20110506

DOCDB simple family (application)

**US 2009037213 W 20090316**; CN 200980109431 A 20090316; EP 09721438 A 20090316; JP 2011500880 A 20090316