

Title (en)
Mast

Title (de)
Mast

Title (fr)
Mât

Publication
EP 2261444 A1 20101215 (DE)

Application
EP 10160975 A 20100426

Priority
DE 202009007463 U 20090526

Abstract (en)
The pole (1) has a base plate (3) for mounting on a subsurface at a lower end of the pole. The base plate includes a ring-shaped chamber that is upwardly aligned to the pole and made up of steel. The chamber includes a concave contour in a corner region of the base plate that includes a central ring-shaped opening i.e. elongated hole, in the corner region of the base plate. A longitudinal axis of an elongated hole is approximately diagonal to adjacent edges of the base plate, where the thickness of the base plate is of 10 millimeters.

Abstract (de)
Mast (1), insbesondere Beleuchtungs-, Antennen- oder Leitungsmast, der an seinem unteren Ende eine Fußplatte (3) zur Verankerung auf einem Untergrund aufweist, wobei die Fußplatte (3) eine aufwärts zum Mast (1) gerichtete im Wesentlichen kreisförmige Wölbung (4) aufweist.

IPC 8 full level
E04H 12/08 (2006.01); **E04H 12/22** (2006.01)

CPC (source: EP)
E04H 12/08 (2013.01); **E04H 12/2261** (2013.01)

Citation (search report)

- [X] GB 1190722 A 19700506 - P R I C PATENT RES INTERNATION [PA]
- [X] WO 2004033803 A1 20040422 - PACIFIC CASCADE PARKING EQUIPM [US], et al
- [X] US 198072 A 18771211 - BONZANO ADOLPHUS
- [A] FR 2484511 A1 19811218 - PETITJEAN ET CIE [FR]

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA ME RS

DOCDB simple family (publication)
DE 202009007463 U1 20090820; DK 2261444 T3 20130923; EP 2261444 A1 20101215; EP 2261444 B1 20130612; ES 2427622 T3 20131031; HR P20130855 T1 20131025; PL 2261444 T3 20131231; PT 2261444 E 20130909; SI 2261444 T1 20131129

DOCDB simple family (application)
DE 202009007463 U 20090526; DK 10160975 T 20100426; EP 10160975 A 20100426; ES 10160975 T 20100426; HR P20130855 T 20130911; PL 10160975 T 20100426; PT 10160975 T 20100426; SI 201030339 T 20100426