

Title (en)
SPACER HAVING A DRYING AGENT FOR AN INSULATED GLASS PANE

Title (de)
ABSTANDSHALTER MIT TROCKNUNGSMITTEL FÜR EINE ISOLIERGLASSCHEIBE

Title (fr)
ÉCARTEUR AVEC UN AGENT DE SÉCHAGE POUR UN VITRAGE ISOLANT

Publication
EP 2262970 A1 20101222 (DE)

Application
EP 09711684 A 20090218

Priority
• EP 2009001155 W 20090218
• DE 102008010271 A 20080219
• DE 102008034027 A 20080716

Abstract (en)
[origin: WO2009103511A1] In order to configure an insulated glass pane, two individual glass panes (2, 3) are glued to each other by means of a frame-shaped spacer (4). For this purpose a sealant is provided in joints (15, 16) between two flanks (7, 8) of the spacer (4) and the two adjoining glass panes (2, 3). The joints (15, 16) on the interior of the insulated glass pane (1) are open and contain a mass (12), which has a surface facing the interior of the insulated glass pane (1) and in which a drying agent is embedded.

IPC 8 full level
E06B 3/663 (2006.01)

CPC (source: EP US)
E06B 3/66342 (2013.01 - EP US); **E06B 3/66361** (2013.01 - EP US); **Y10T 29/49** (2015.01 - US)

Citation (search report)
See references of WO 2009103511A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
WO 2009103511 A1 20090827; CA 2715337 A1 20090827; EP 2262970 A1 20101222; US 2010330310 A1 20101230;
US 2011296796 A1 20111208; US 8530010 B2 20130910; US 8769889 B2 20140708

DOCDB simple family (application)
EP 2009001155 W 20090218; CA 2715337 A 20090218; EP 09711684 A 20090218; US 201013201833 A 20100215; US 86800009 A 20090218