

Title (en)  
BIMETALLIC VALVE

Title (de)  
BIMETALLVENTIL

Title (fr)  
SOUPAPE BIMÉTALLIQUE

Publication  
**EP 2262981 B1 20111116 (DE)**

Application  
**EP 10711585 A 20100329**

Priority  
• EP 2010001978 W 20100329  
• DE 102009016833 A 20090409

Abstract (en)  
[origin: WO2010115540A1] The invention relates to a bimetallic valve for an internal combustion engine, comprising a valve body (3) consisting of an iron-base alloy and a sheath body (4) in the region of the valve head (1), consisting of a cobalt-base or nickel-base alloy, the thermal expansion of the valve body being considerably higher than that of the sheath body (4). The difference between the thermal expansions  $\alpha(20^{\circ}\text{-T})$  of the valve body (3) and the sheath body (4) is at least  $2\mu\text{m/mK}$  according to the formula  $(\alpha_{VK} - \alpha_{HK}) > 2$ . The valve body (3) and the sheath body (4) are interconnected by welding, and a residual compressive stress is produced in the sheath body at room temperature, by heating the valve body (3) and the sheath body (4), following the welding, above the yield point of the sheath body (4), with plastic deformation of same, and then subsequently cooling said bodies.

IPC 8 full level  
**F01L 3/02** (2006.01); **F01L 3/04** (2006.01)

CPC (source: EP)  
**F01L 3/02** (2013.01); **F01L 3/04** (2013.01)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)  
**WO 2010115540 A1 20101014**; AT E533927 T1 20111215; DE 102009016833 B3 20110113; DK 2262981 T3 20120102;  
EP 2262981 A1 20101222; EP 2262981 B1 20111116; SG 175141 A1 20111229

DOCDB simple family (application)  
**EP 2010001978 W 20100329**; AT 10711585 T 20100329; DE 102009016833 A 20090409; DK 10711585 T 20100329; EP 10711585 A 20100329;  
SG 2011073574 A 20100329