

Title (en)
Device for handling food

Title (de)
Vorrichtung zur Behandlung von Lebensmitteln

Title (fr)
Dispositif de traitement de produits alimentaires

Publication
EP 2269463 A3 20110831 (DE)

Application
EP 10164159 A 20100527

Priority
DE 102009026500 A 20090527

Abstract (en)
[origin: EP2269463A2] The apparatus comprises a rotating device (104) arranged partially in an interior of the apparatus with a rotation-symmetrical atomization element for mechanically atomizing liquids. The atomization element is formed, so that the liquid fed to the atomization element is mechanically atomized based on the rotation of the atomization element, where the desired atomization is adjustable by the selection of adequate rotational speed of the atomization element. The rotating device is movably mounted inside the apparatus. The atomization element is an atomizer plate (106). The apparatus comprises a rotating device (104) arranged partially in an interior of the apparatus with a rotation-symmetrical atomization element for mechanically atomizing liquids. The atomization element is formed, so that the liquid fed to the atomization element is mechanically atomized based on the rotation of the atomization element, where the desired atomization is adjustable by the selection of adequate rotational speed of the atomization element. The rotating device is movably mounted inside the apparatus. The atomization element is an atomizer plate (106) with a plane surface or a bell-shaped atomizer plate. The atomization element is directly driven by an electric motor. The apparatus includes a supply device for supplying the atomization element with liquid at front side of the atomization element. The atomization element has an opening in the area of the rotation axis for a liquid feedthrough to feed the liquid to the atomization element from its rear side. The rotating device has a separate rotary feedthrough with a first coupling area for connecting the liquid feedthrough and a second coupling area for connecting an external water line. The rotary feedthrough has a gap sealing, stages in the form of a radial diameter difference opposite to the liquid feedthrough, and Archimedes screw. The rotating device has a drivable element such as a pulley (112) and/or a driving shaft arranged in the area of the rotation axis, and is positively, non-positively and/or materially connected with a housing wall of the apparatus for treating the food products. The atomization element is arranged at the inner side of a fermentation cabinet nearer to the rear wall, so that the rotation axis of the atomization element horizontally runs. An independent claim is included for a method for operating an apparatus for treating food products.

IPC 8 full level
A21B 3/04 (2006.01); **A21C 13/00** (2006.01); **F24C 15/32** (2006.01)

CPC (source: EP)
A21B 3/04 (2013.01); **A21C 13/00** (2013.01); **F24C 14/005** (2013.01); **F24C 15/327** (2013.01)

Citation (search report)

- [XAI] EP 0244538 A2 19871111 - LINCOLN FOODSERVICE [US]
- [XY] EP 0523489 A1 19930120 - ZANUSSI GRANDI IMPIANTI SPA [IT]
- [Y] FR 2599280 A1 19871204 - AMELIORAIR SA [FR], et al

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
BA ME RS

DOCDB simple family (publication)
EP 2269463 A2 20110105; EP 2269463 A3 20110831; DE 102009026500 B3 20110224

DOCDB simple family (application)
EP 10164159 A 20100527; DE 102009026500 A 20090527