

Title (en)  
Locking device and drawer slide

Title (de)  
Rastbeschlag und Auszugsführung

Title (fr)  
Dispositif de verrouillage et glissière

Publication  
**EP 2272400 B1 20190220 (DE)**

Application  
**EP 10166988 A 20100623**

Priority  
• DE 202009005008 U 20090709  
• DE 202009005256 U 20090909

Abstract (en)  
[origin: EP2272400A1] The device has a cam segment in which a switching element (10) is guided. The segment has a loop at which a locking recess for the switching element is provided, where the switching element is pre-stressed by a force accumulator i.e. compression spring (63), in a locking position. The locking recess is partially supported in a displaceable and/or pivotable manner, and the switching element is released from the locking position. The recess has two movable parts pre-stressed by a spring in an initial position, rotatable around an axis and movably supported along a linear guide.

IPC 8 full level  
**A47B 88/463** (2017.01); **E05C 19/02** (2006.01)

CPC (source: EP)  
**A47B 88/463** (2016.12); **E05C 19/022** (2013.01); **E05B 65/46** (2013.01)

Cited by  
DE102011002212A1; US9295329B2; JP2014516649A; CN111148453A; US2015097473A1; JP2015521924A; EP3260014A1; CN110801975A; DE202020100792U1; EP2532272A1; CN106901524A; US8807671B2; WO2019057527A1; WO2014008522A1; US9215929B2; US9532648B2; DE102012112675A1; WO2013104522A1; US9277815B2; DE102021110323A1; US9375083B2; DE102018105116A1; WO2019170619A1; WO2022157295A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)  
**DE 202009005256 U1 20101125**; EP 2272400 A1 20110112; EP 2272400 B1 20190220; ES 2727330 T3 20191015; PL 2272400 T3 20190830

DOCDB simple family (application)  
**DE 202009005256 U 20090909**; EP 10166988 A 20100623; ES 10166988 T 20100623; PL 10166988 T 20100623