

Title (en)

Method and device for continuous combining of at least two layer transport flows of flat printed products

Title (de)

Verfahren und Vorrichtung zum kontinuierlichen Zusammenführen von zumindest zwei Schuppenströmen flächiger Druckprodukte

Title (fr)

Procédé et dispositif d'assemblage continu d'au moins deux flux de tuiles de produits d'impression plats

Publication

EP 2275373 B1 20121226 (DE)

Application

EP 09165698 A 20090716

Priority

EP 09165698 A 20090716

Abstract (en)

[origin: EP2275373A1] The method involves initially offsetting an imbricated flow (2a) of flat printed products (3) relative to another imbricated flow (2b) of the printed products, so as to form a lateral overlapping area of the imbricated flows. The printed products are continuously lifted in the lateral overlapping area until the lateral overlapping is eliminated. The printed products are lowered or dropped, so that one of the printed products rests above the imbricated flows above the other printed product, where a single imbricated flow with another overlapping area of the printed products is formed. An independent claim is also included for a device for continuous combining of two layer transport flows of flat printed products.

IPC 8 full level

B65H 29/66 (2006.01)

CPC (source: EP US)

B65H 29/6681 (2013.01 - EP US); **B65H 2404/2613** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

EP 2275373 A1 20110119; **EP 2275373 B1 20121226**; CN 101955082 A 20110126; CN 101955082 B 20150923; JP 2011020857 A 20110203; JP 5616151 B2 20141029; US 2011014024 A1 20110120

DOCDB simple family (application)

EP 09165698 A 20090716; CN 201010232500 A 20100716; JP 2010162344 A 20100716; US 83821910 A 20100716