

Title (en)

METHOD AND DEVICE FOR UNLOADING OF A CONTAINER WITH AN APERTURE

Title (de)

VERFAHREN UND VORRICHTUNG ZUM ENTLADEN EINES BEHÄLTERS MIT EINER ÖFFNUNG

Title (fr)

PROCÉDÉ ET DISPOSITIF POUR DÉCHARGEMENT D'UN CONTENEUR AVEC UNE OUVERTURE

Publication

EP 2276687 A4 20130424 (EN)

Application

EP 09729846 A 20090409

Priority

- SE 2009050375 W 20090409
- SE 0800808 A 20080410

Abstract (en)

[origin: WO2009126109A1] A method for unloading a container (1) comprises presenting and locking of the container to a retaining means (3) with the aperture in the container against a means (5) which closes the aperture and with the lower edge of the aperture level or substantially level with a substrate (6) for the retaining means, moving of the retaining means with container locked to it and the means which closes the aperture in the container from presenting and locking position to a preparatory position (B) for unloading of the container with the container's aperture directed substantially downwards and goods in the container resting upon the means which closes the aperture, and moving of the means which closes the container's aperture relative to the retaining means with container locked to it, for progressive exposure of the container's aperture and the goods in the container resting upon the means which closes the aperture, in such a way that the exposed goods fall down onto a device (10) for carrying the goods away. During the movement of the retaining means (3) with container (1) locked to it and the means (5) which closes the aperture in the container, from the presenting and locking position to the preparatory position (B) for unloading of the container, the retaining means with the container and the means which closes the container are tilted in such a way that the lower edge of the aperture in the container remains level or substantially level with the substrate (6) for the retaining means, and during movement of the means which closes the container's aperture relative to the retaining means with container locked to it, the container's aperture and the goods in the container are progressively exposed, while at the same time the retaining means with container locked to it is caused to remain in the preparatory position for unloading of the container with the lower edge of the container aperture level or substantially level with the substrate (6) for the retaining means. The present invention relates also to a device for unloading of a container as above.

IPC 8 full level

B65G 65/23 (2006.01)

CPC (source: EP)

B65G 65/23 (2013.01); **B65G 2201/0264** (2013.01)

Citation (search report)

- [XAI] US 3754671 A 19730828 - WALDA F
- [AP] DE 102007024670 A1 20081204 - DEUTSCHE POST AG [DE]
- [E] EP 2281762 A1 20110209 - RED PARCEL POST AG [DE]
- [A] FR 2224347 A1 19741031 - REXNORD INC [SU]
- [A] FR 2824545 A1 20021115 - JOLLY LUC FRANCOIS MARIE [FR]
- [A] FR 2429734 A1 19800125 - SALAH LUCIEN [FR]
- See references of WO 2009126109A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2009126109 A1 20091015; EP 2276687 A1 20110126; EP 2276687 A4 20130424

DOCDB simple family (application)

SE 2009050375 W 20090409; EP 09729846 A 20090409