

Title (en)

METHOD FOR THE REMOVAL OF BALLAST FROM A TRACK

Title (de)

VERFAHREN ZUM ENTFERNEN VON SCHOTTER EINES GLEISES

Title (fr)

PROCÉDÉ D'ENLÈVEMENT DE BALLAST D'UN RAIL

Publication

EP 2286029 B1 20150107 (DE)

Application

EP 09737789 A 20090402

Priority

- EP 2009002409 W 20090402
- AT 2482008 U 20080428

Abstract (en)

[origin: WO2009132745A1] In order to remove ballast (10) from a first ballast bed (3) of a first track, ballast removing devices (11, 12) are guided along a second track (4) running parallel to the ballast bed (3). Ballast (10) located in a section (18) adjoining a second ballast bed (5) of the second track (4) is received separately from the remaining ballast (10) of the first ballast bed (3), thus allowing the entire ballast (10) to be removed.

IPC 8 full level

E01B 27/04 (2006.01); **E01B 27/08** (2006.01)

CPC (source: EP)

E01B 27/04 (2013.01)

Cited by

CN104484692A; CN104463073A; CN104966121A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)

AT 10057 U2 20080815; **AT 10057 U3 20090515**; DK 2286029 T3 20150413; EP 2286029 A1 20110223; EP 2286029 B1 20150107; ES 2534238 T3 20150420; PL 2286029 T3 20150630; WO 2009132745 A1 20091105

DOCDB simple family (application)

AT 2482008 U 20080428; DK 09737789 T 20090402; EP 09737789 A 20090402; EP 2009002409 W 20090402; ES 09737789 T 20090402; PL 09737789 T 20090402