

Title (en)
RETAINER, DEEP GROOVE BALL BEARING, AND BEARING WITH SEAL

Title (de)
HALTER, RILLENKUGELLAGER UND LAGER MIT ABDICHTUNG

Title (fr)
DISPOSITIF DE RETENUE, ROULEMENT À BILLES À GORGE PROFONDE, ET ROULEMENT À JOINT

Publication
EP 2287481 A4 20150422 (EN)

Application
EP 09762365 A 20090526

Priority
• JP 2009059558 W 20090526
• JP 2008155909 A 20080613
• JP 2008178620 A 20080709

Abstract (en)
[origin: EP2287481A1] Provided are a retainer capable of achieving torque reduction, a deep-groove ball bearing with the retainer, and a sealed bearing capable of preventing intrusion of foreign matter into the bearing and capable of sufficient seal torque reduction. The retainer is formed by combination of two annular retaining plates (27A, 27B) each including semispherical swelling portions (26) arranged at predetermined intervals along a circumferential direction. The semispherical swelling portions (26, 26) face each other and form pockets (30) for retaining balls (16). Each of the pockets (30) has ball-facing surfaces each including a ball non-contact portion (31), and a contact area in each of the pockets (30) with respect to each of the balls (16) is reduced by from 15% to 30% in comparison with a contact area with respect to each of the balls (16) without provision of the ball non-contact portion (31). Each of the seal members (17) serves as a contact seal having a seal lip portion (17a) coming into contact with another of raceway, and a material of at least a distal end of the seal lip portion (17a) includes a high-abrasion material which is prone to abrasion.

IPC 8 full level
F16C 33/42 (2006.01); **F16C 33/78** (2006.01); **F16C 33/66** (2006.01)

CPC (source: EP US)
F16C 33/3887 (2013.01 - EP US); **F16C 33/427** (2013.01 - EP US); **F16C 33/6681** (2013.01 - EP US); **F16C 33/7823** (2013.01 - EP US); **F16C 33/7853** (2013.01 - EP US); **F16C 19/06** (2013.01 - EP US); **F16C 2361/61** (2013.01 - EP US)

Citation (search report)
• [X] US 4958946 A 19900925 - VOLL HORST [DE]
• [X] JP 2002303326 A 20021018 - NSK LTD
• [XY] JP 2006226448 A 20060831 - NTN TOYO BEARING CO LTD
• [X] US 1494012 A 19240513 - PARSONS HARRY N
• [X] US 1712222 A 19290507 - LINDE ANDREW H
• [X] SU 765540 A1 19800923 - STRAMNOV ANATOLIY T [SU]
• [X] DE 296238 C
• [X] SU 461254 A1 19750225
• [X] JP H09273557 A 19971021 - KOYO SEIKO CO
• [Y] US 4428629 A 19840131 - COLANZI FRANCO [IT], et al
• [Y] US 3572857 A 19710330 - HASEGAWA HISAO
• [Y] DE 2803093 A1 19790726 - STEYR DAIMLER PUCH AG
• See references of WO 2009150935A1

Cited by
WO2014203103A1; ITTO20130464A1; CN105358849A; KR20160013061A; US9488227B2; WO2016043853A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 2287481 A1 20110223; EP 2287481 A4 20150422; EP 2287481 B1 20170208; BR 122019024860 B1 20210511;
BR PI0915147 A2 20160621; BR PI0915147 A8 20191224; BR PI0915147 B1 20200915; BR PI0915147 B8 20211109;
CN 102066786 A 20110518; CN 102066786 B 20150422; EP 3179122 A1 20170614; EP 3179122 B1 20200212; US 2011069918 A1 20110324;
US 8727631 B2 20140520; WO 2009150935 A1 20091217

DOCDB simple family (application)
EP 09762365 A 20090526; BR 122019024860 A 20090526; BR PI0915147 A 20090526; CN 200980122270 A 20090526;
EP 17153050 A 20090526; JP 2009059558 W 20090526; US 99352009 A 20090526