

Title (en)
DECORATIVE SHEET, PROCESS FOR PRODUCING DECORATIVE RESIN MOLDED PRODUCT

Title (de)
ZIERFOLIE, VERFAHREN ZUR HERSTELLUNG EINES DEKORATIVEN KUNSTHARZFORMPRODUKTS

Title (fr)
FEUILLE DÉCORATIVE, PROCÉDÉ DE FABRICATION DE PRODUIT MOULÉ EN RÉSINE DÉCORATIVE

Publication
EP 2298526 A1 20110323 (EN)

Application
EP 09773445 A 20090629

Priority

- JP 2009061882 W 20090629
- JP 2008171647 A 20080630
- JP 2008171648 A 20080630
- JP 2009088073 A 20090331
- JP 2009088075 A 20090331

Abstract (en)

The present invention relates to a decorative sheet for insert molding prepared by laminating at least a surface protective layer on a support comprising an ABS resin, wherein the above support has a flexural modulus of 1500 to 3000 MPa; the above support has a thickness of 100 to 500 μm ; the above surface protective layer is obtained by cross-linking and curing an ionizing radiation curable resin composition; and the above ionizing radiation curable resin composition has a tensile modulus of more than 100 MPa to less than 1000 MPa which is measured by the following method and a static frictional coefficient of 1.0 or less on a surface and a decorative sheet for insert molding comprising at least a picture layer, a low glossy picture ink layer provided partially and a surface protective layer in this order on a support, wherein the above surface protective layer is present on the low glossy picture ink layer and brought into contact therewith, and it is coated over a whole surface including an area where the above low glossy picture ink layer is formed and an area where the low glossy picture ink layer is not formed; the surface protective layer is obtained by cross-linking and curing an ionizing radiation curable resin composition; and the surface protective layer has a thickness of 1 to 30 μm . Capable of being provided are a decorative sheet which has a high abrasion resistance and a high scratch resistance and is provided with a good moldability and which has a surface protective layer causing no cracks and is provided with a high design property and used for molding a decorated molding, a production process for a decorated resin molding by using the above decorative sheet and a decorated resin molding produced by the above production process.

IPC 8 full level
B29C 45/14 (2006.01); **B32B 27/00** (2006.01); **B29L 7/00** (2006.01)

CPC (source: EP US)
B29C 45/1418 (2013.01 - EP US); **B29C 45/14688** (2013.01 - EP US); **B29C 45/14811** (2013.01 - EP US); **B29C 2045/14245** (2013.01 - EP US); **B29K 2633/08** (2013.01 - EP US); **B29K 2995/0087** (2013.01 - EP US); **B29L 2031/286** (2013.01 - EP US); **B29L 2031/3041** (2013.01 - EP US); **B29L 2031/724** (2013.01 - EP US); **B29L 2031/778** (2013.01 - EP US); **Y10T 428/24851** (2015.01 - EP US); **Y10T 428/264** (2015.01 - EP US); **Y10T 428/265** (2015.01 - EP US); **Y10T 428/266** (2015.01 - EP US); **Y10T 428/31855** (2015.04 - EP US); **Y10T 428/31909** (2015.04 - EP US)

Cited by
EP3466677A4; EP2960039A1; US10946610B2; US10279520B2; JP2014069447A; JP2013082221A; EP3440142B1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
EP 2298526 A1 20110323; **EP 2298526 A4 20121031**; **EP 2298526 B1 20190403**; CN 102066075 A 20110518; CN 102066075 B 20140917; KR 101599568 B1 20160303; KR 20110037933 A 20110413; US 2011143128 A1 20110616; US 2014065384 A1 20140306; US 8597793 B2 20131203; US 9440383 B2 20160913; WO 2010001867 A1 20100107

DOCDB simple family (application)
EP 09773445 A 20090629; CN 200980113057 A 20090629; JP 2009061882 W 20090629; KR 20107024806 A 20090629; US 201314075985 A 20131108; US 99173809 A 20090629