

Title (en)
FIRST OPENING SAFETY

Title (de)
ERSTÖFFNUNGSSICHERUNG

Title (fr)
DISPOSITIF DE SÉCURITÉ DE PREMIÈRE OUVERTURE

Publication
EP 2307298 A1 20110413 (DE)

Application
EP 09780987 A 20090723

Priority
• EP 2009059499 W 20090723
• DE 102008036718 A 20080807

Abstract (en)
[origin: WO2010015519A1] The invention relates to a first opening safety (101) for mounting onto adhesive or correction rollers (201) for applying an adhesive or corrective film (206) onto a substrate (301) by way of an application device (203), wherein the first opening safety (101) extends at least partially over the application device (203) in the installed state and is disposed at least partially between the adhesive or correction film (206) and the substrate (301) in order to prevent application of the adhesive or correction film (206) onto the substrate (301) by way of the application device (203), and wherein the first opening safety (101) can be released from the adhesive or correction roller (201) for first time use of the adhesive or correction roller (101) so that the first opening safety (101) can be removed prior to the first time transfer of the adhesive or correction film (206) onto the substrate (301) by way of the application device (203). In this way, wrap-around packaging can be conserved and trial usage by users in sales areas can be eliminated.

IPC 8 full level
B65H 37/00 (2006.01)

CPC (source: EP)
B65H 37/007 (2013.01)

Citation (search report)
See references of WO 2010015519A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)
AL BA RS

DOCDB simple family (publication)
WO 2010015519 A1 20100211; AT E556969 T1 20120515; DE 102008036718 A1 20100218; EP 2307298 A1 20110413;
EP 2307298 B1 20120509

DOCDB simple family (application)
EP 2009059499 W 20090723; AT 09780987 T 20090723; DE 102008036718 A 20080807; EP 09780987 A 20090723