

Title (en)  
SWITCHING DEVICE

Title (de)  
SCHALTGERÄT

Title (fr)  
DISPOSITIF DE COMMUTATION

Publication  
**EP 2313905 B1 20120404 (DE)**

Application  
**EP 09775551 A 20090702**

Priority  
• AT 2009000260 W 20090702  
• AT 11902008 A 20080731

Abstract (en)  
[origin: US2010026430A1] A switching device has a magnetic tripping arrangement which includes at least one armature, a coil a yoke, and a yoke sleeve which is formed by at least one first bent part. The armature and the yoke sleeve are hereby arranged in a substantially flush manner, with the coil being arranged substantially around the armature and/or the yoke sleeve. The yoke is arranged about the coil, and the armature is formed for at least indirectly tripping a disconnecting apparatus of the switching device.

IPC 8 full level  
**H01H 71/24** (2006.01); **H01H 69/00** (2006.01)

CPC (source: AT EP US)  
**H01H 71/24** (2013.01 - AT); **H01H 71/2454** (2013.01 - EP US); **H01H 71/2463** (2013.01 - EP US); **H01H 69/00** (2013.01 - AT)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

Designated extension state (EPC)  
BA

DOCDB simple family (publication)  
**US 2010026430 A1 20100204**; AT 509279 A1 20110715; AT 517193 A5 20161115; AT E552605 T1 20120415; AU 2009276298 A1 20100204; AU 2009276298 B2 20150903; CN 102113079 A 20110629; CN 102113079 B 20140528; EP 2313905 A1 20110427; EP 2313905 B1 20120404; ES 2384913 T3 20120713; PL 2313905 T3 20121031; RU 2011107218 A 20120910; RU 2523717 C2 20140720; WO 2010012012 A1 20100204; WO 2010012012 A8 20100408

DOCDB simple family (application)  
**US 51251409 A 20090730**; AT 09775551 T 20090702; AT 11902008 A 20080731; AT 2009000260 W 20090702; AT 92662009 A 20090702; AU 2009276298 A 20090702; CN 200980130531 A 20090702; EP 09775551 A 20090702; ES 09775551 T 20090702; PL 09775551 T 20090702; RU 2011107218 A 20090702