

Title (en)

Method for operating a recooling circuit with a hybrid cooler for an assembly with discontinuous heat discharge

Title (de)

Verfahren zum Betreiben eines Rückkühlkreislaufes mit einem Hybridkühler für eine Anlage mit einer diskontinuierlichen Wärmeabgabe

Title (fr)

Procédé de fonctionnement d'un circuit de refroidissement de recirculation doté d'un refroidisseur hybride pour une installation ayant une sortie de chaleur discontinue

Publication

**EP 2320189 B1 20200722 (DE)**

Application

**EP 10188007 A 20101019**

Priority

- DE 102009051888 A 20091104
- DE 102010008408 A 20100218

Abstract (en)

[origin: EP2320189A2] The method involves spray regulation of a hybrid cooler (2) i.e. dry cooler, and continuously detecting actual operating parameters e.g. actual temperature, of a system (3) i.e. adsorption refrigerator. The detected operating parameters are compared with a preset value in a regulation unit (17). A spray device (18) of the hybrid cooler is activated when reaching and/or exceeding the preset value by the actual detected operating parameters until reaching or exceeding another preset value. The actual temperature within a recooling circuit (1) is detected. An independent claim is also included for a device for operating a recooling circuit.

IPC 8 full level

**F28F 27/00** (2006.01); **F25B 17/08** (2006.01); **F28D 5/02** (2006.01)

CPC (source: EP)

**F25B 49/046** (2013.01); **F28D 5/02** (2013.01); **F28F 27/003** (2013.01); **F24F 5/0014** (2013.01); **F25B 17/083** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 2320189 A2 20110511**; **EP 2320189 A3 20140903**; **EP 2320189 B1 20200722**; DE 102010008408 A1 20110714;  
DE 102010008408 B4 20190711; ES 2820876 T3 20210422

DOCDB simple family (application)

**EP 10188007 A 20101019**; DE 102010008408 A 20100218; ES 10188007 T 20101019